


## PCM-RF Signal Processing

### Description

The CX20102 is a bipolar IC which has been developed for the processing of PCM audio RF signals of the 8 mm VTR, and consists of the following functions:

- Recording system : Limiter, and Area selector switch
- Playback system : Voltage follower for RF equalizer, Limiter, Tri-state TTL buffer, PLL, and D-FF

20-pin SOP (Plastic)



### Features

- Single 5V ( $5.0 \pm 0.25$ V) power supply operation.
- Low power consumption (85mW typical in a REC mode, and 110 mW typical in a PB mode)
- Built-in power saving functions

### Absolute Maximum Ratings (Ta=25°C)


- Power supply voltage      Vcc      10      V
- Operating temperature      Topr      -20 to +75      °C
- Storage temperature      Tstg      -55 to +150      °C
- Allowable power dissipation      Pd      690      mW

### Recommended Operating Condition

4.75 to 5.25      V

Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.

## Block Diagram



**Pin Description**

No.	Name	Description
1	DUTY	Fine adjustment of the input waveform sampling phase Normally open
2	Loop filter 1	Connects an external loop filter time constant
3	Loop filter 2	Connects an external loop filter time constant
4	F $\phi$ ADJ	Adjusting pin of the VCO free running frequency
5	REF R	R externally attached VCO current source
6	Vcc <sub>2</sub>	Digital Vcc
7	STBY	Power saving control pin; standby at L (CMOS level)
8	FMCK	Clock output
9	GND2	Digital GND
10	FMDT	Data input/output
11	MODE	REC/PB selector pin (CMOS level)
12	REC RF	REC mode RF output (LIM OUT)
13	REC AREA	REC AREA output (CMOS level)
14	AREA	AREA input 2 ( CMOS level)
15	LIM IN2	Limiter input
16	Vcc <sub>1</sub>	Analog Vcc
17	LIM IN1	Limiter input 1
18	LPF	Voltage follower output
19	GND1	Analog GND
20	RBRF	Voltage follower input

## Electrical Characteristics

See Measuring Circuit Diagram 2

Ta=25°C, Vcc=5 V;





Item	Symbol	Condition	Min.	Typ.	Max.	Unit
PB current consumption	IccPB	Pins ⑦ and ⑪ : H		19	25	mA
REC current consumption	IccREC	Pin ⑦ : H		16	20	mA
PB standby current	IccST			12	15	mA
Clock capture range	C.Rck	Pins ⑦ and ⑪ : H	11.0		12.0	MHz
Output level	V <sub>OH</sub>	1. With pin ① open, adjust the free running frequency at 11.5MHz	2.2			V
Pins ⑧ and ⑩	V <sub>OL</sub>	2. Input 50mV 11MHz and 12MHz from pin ① and perform measurement			0.8	V
Data clock delay time *1	t <sub>pd</sub>		4		35	nS
Operating input voltage	V <sub>IN</sub>		50			mVp-p
Output level Pin ⑬	V <sub>OH</sub>	Pins ⑦ and ⑭ : H	3.5			V
	V <sub>OL</sub>	Pins ⑦ : H or Pins ⑦, ⑭ and ⑪ : H or Pins ⑦ and ⑪ : H			1.5	V
Input current	I <sub>IH</sub>	Input voltage: 4V		120	200	μA
Pins ⑦ and ⑭	I <sub>IL</sub>	Input voltage: 0V	-2	0	+2	μA
Operating input voltage	V <sub>IH</sub>		3.5			V
Pins ⑦ and ⑭	V <sub>IL</sub>				1.5	V
Input current Pin ⑩	I <sub>IH</sub>	Input voltage: 5V			60	μA
	I <sub>IL</sub>	Input voltage: 0V	-2	0	2	μA
Operating input voltage	V <sub>IH</sub>		2.5			V
Pin ⑩	V <sub>IL</sub>				1.5	V
Input current Pin ⑪	I <sub>IH</sub>	Input voltage: 3.5V		130	200	
	I <sub>IL</sub>	Input voltage: 0V	-2	0	2	
Operating input voltage	V <sub>IH</sub>		2.5			V
Pin ⑪	V <sub>IL</sub>				0.8	V
Voltage follower gain	G <sub>VF</sub>	Pins ⑦ and ⑪ : H Input: Pin ⑯ 6MHz, 0.6Vp-p Output: Pin ⑮	-1.5	0	1	dB
REC RF LIM output	V <sub>LIM</sub>	Pins ⑦ and ⑭ : H Input: Pin ⑩ TTL level input Output: Pin ⑫	0.40	0.50	0.56	Vp-p

\*1 For t<sub>pd</sub> measurements, see Fig. 3 Timing Chart.

## Truth Table

Operation State	Pin 7	Pin 11	Pin 14
Power saving	L	X	X
PB	H	H	X
REC	H	L	H
REC standby	H	L	L

X: Don't care

**Fig. 1 Operating description****PB****REC, REC STBY****Fig. 2 Electrical characteristics measuring circuit****Fig. 3 tpd measurement**

## Standard Circuit Designing Data


Standard pin voltage (DC): See Fig. 2

No.	Voltage	No.	Voltage
1	3.8V	11	5*V or 0V
2	4.3V	12	3.7 to 4.2V
3	4.3V	13	0 or 4.2V
4	4.85*V	14	5*V or 0V
5	0.2V	15	2.3V
6	5.0*V (Vcc)	16	5.0*V (Vcc)
7	5*V or 0V	17	2.3V
8	Clock output	18	2.3V
9	0* (GND)	19	0*V (GND)
10	Data output	20	2.3V

\*: Externally applied

During PB mode (Pins ⑦ and ⑪: H)

Fig. 4 Application circuit



Application circuits shown are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits or for any infringement of third party patent and other right due to same.

Fig. 5 Free running frequency vs.  
Power supply voltage




Fig. 6 Pin ⑦ current vs. Voltage




Fig. 7 Pin ⑪ current vs. Voltage







Fig. 8 Pin ⑭ current vs. Voltage




**Fig. 9 Free running frequency vs.  
Pin ④ voltage**



**Fig. 10 Free running frequency vs.  
Ambient temperature**




**Fig. 11 Free running frequency vs.  
Power supply voltage**



## Package Outline      Unit : mm

20PIN SOP (PLASTIC) 300MIL



## PACKAGE STRUCTURE

SONY CODE	SOP-20P-L01
EIAJ CODE	*SOP020-P-0300-A
JEDEC CODE	_____

PACKAGE MATERIAL	EPOXY RESIN
LEAD TREATMENT	SOLDER PLATING
LEAD MATERIAL	COPPER ALLOY
PACKAGE WEIGHT	0.3g