

## LOW DROP POWER SCHOTTKY RECTIFIER

### MAIN PRODUCT CHARACTERISTICS

<b>I<sub>F(AV)</sub></b>	<b>2 A</b>
<b>V<sub>RRM</sub></b>	<b>30 V</b>
<b>T<sub>j (max)</sub></b>	<b>150 °C</b>
<b>V<sub>F (max)</sub></b>	<b>0.375 V</b>

### FEATURES AND BENEFITS

- LOW COST DEVICE WITH LOW DROP FORWARD VOLTAGE FOR LESS POWER DISSIPATION.
- OPTIMIZED CONDUCTION/REVERSE LOSSES TRADE-OFF WHICH LEADS TO THE HIGHEST YIELD IN THE APPLICATIONS.
- HIGH POWER SURFACE MOUNT MINIATURE PACKAGE.
- AVALANCHE CAPABILITY SPECIFIED

### DESCRIPTION


Single Schottky rectifier suited to Switched Mode Power Supplies and high frequency DC to DC converters, freewheel diode and integrated circuit latch up protection.

Packaged in SMA, this device is especially intended for use in parallel with MOSFETs in synchronous rectification.

### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage		30	V
I <sub>F(RMS)</sub>	RMS forward current		10	A
I <sub>F(AV)</sub>	Average forward current	T <sub>L</sub> = 120°C δ = 0.5	2	A
I <sub>FSM</sub>	Surge non repetitive forward current	tp = 10 ms Sinusoidal	75	A
I <sub>R(RM)</sub>	Repetitive peak reverse current	tp = 2 μs F = 1kHz square	1	A
I <sub>R(SM)</sub>	Non repetitive peak reverse current	tp = 100 μs square	1	A
P <sub>ARM</sub>	Repetitive peak avalanche power	tp = 1 μs T <sub>j</sub> = 25°C	1500	W
T <sub>stg</sub>	Storage temperature range		- 65 to + 150	°C
T <sub>j</sub>	Maximum operating junction temperature *		150	°C
dV/dt	Critical rate of rise of reverse voltage		10000	V/μs

\* :  $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$  thermal runaway condition for a diode on its own heatsink



# STPS2L30A

## THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-l)}$	Junction to lead	30	°C/W

## STATIC ELECTRICAL CHARACTERISTICS


Symbol	Parameters	Tests Conditions	Min.	Typ.	Max.	Unit	
$I_R^*$	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			200	$\mu\text{A}$
		$T_j = 100^\circ\text{C}$			6	15	mA
$V_F^*$	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 2\text{ A}$			0.45	V
		$T_j = 125^\circ\text{C}$			0.325	0.375	
		$T_j = 25^\circ\text{C}$	$I_F = 4\text{ A}$			0.53	
		$T_j = 125^\circ\text{C}$			0.43	0.51	

Pulse test : \*  $t_p = 380\ \mu\text{s}$ ,  $\delta < 2\%$


To evaluate the conduction losses use the following equation :

$$P = 0.24 \times I_{F(AV)} + 0.068 I_{F(RMS)}^2$$


**Fig. 1:** Average forward power dissipation versus average forward current.




**Fig. 2:** Average forward current versus ambient temperature ( $\delta=0.5$ ).




**Fig. 3:** Normalized avalanche power derating versus pulse duration.




**Fig. 4:** Normalized avalanche power derating versus junction temperature.




**Fig. 5:** Non repetitive surge peak forward current versus overload duration (maximum values).




**Fig. 6:** Relative variation of thermal impedance junction to ambient versus pulse duration.




**Fig. 7:** Reverse leakage current versus reverse voltage applied (typical values).




**Fig. 8:** Junction capacitance versus reverse voltage applied (typical values).




**Fig. 9-1:** Forward voltage drop versus forward current (maximum values, high level).




**Fig. 9-2:** Forward voltage drop versus forward current (typical values, low level).



**Fig. 9-3:** Forward voltage drop versus forward current (maximum values, low level).



**Fig. 10:** Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, copper thickness: 35μm).




## PACKAGE MECHANICAL DATA

## SMA

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063

## FOOT PRINT DIMENSIONS (in millimeters)



Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS2L30A	G30	SMA	0.068g	5000	Tape & reel

- BAND INDICATES CATHODE
- EPOXY MEETS UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany  
 Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore  
 Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>