

PQ1CF2

TO-220 Package Chopper Regulator

■ Features


- Maximum switching current : 1.5A
- Built-in ON/OFF control function
- Built-in soft start function
- Built-in oscillation circuit
(oscillation frequency : TYP.100kHz)
- Built-in overheat protection, overcurrent protection function
- TO-220 package
- Variable output voltage
(1.26 to 35V/-1.26 to-30V)
[Possible to choose step down output/inversing output according to external connection circuit]

■ Applications

- Switching power supplies
- Facsimiles
- Printers
- Personal computers

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Rating	Unit
*1 Input voltage	V _{IN}	40	V
Error input voltage	V _{ADJ}	7	V
Input-output voltage	V _{i-o}	41	V
*2 Output-COM voltage	V _{OUT}	-1	V
*3 ON/OFF control voltage	V _C	-0.3 to 40	V
Switching current	I _{sw}	1.5	A
Power dissipation (No heat sink)	P _{D1}	1.5	W
Power dissipation (With infinite heat sink)	P _{D2}	15	W
*4 Junction temperature	T _j	150	°C
Operating temperature	T _{opr}	-20 to +80	°C
Storage temperature	T _{stg}	-40 to +150	°C
Soldering temperature	T _{sol}	260 (For 10s)	°C

*1 Voltage between V_{IN} terminal and COM terminal.*2 Voltage between V_{OUT} terminal and COM terminal.*3 Voltage between V_C terminal and COM terminal.*4 Overheat protection may operate at 125=<T_j<150°C

· Please refer to the chapter "Handling Precautions".

SHARP

" In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest version of the device specification sheets before using any SHARP's device."

■ Electrical Characteristics

(Unless otherwise specified, conditions shall be $V_{IN}=5V$, $I_o=2.5A$, $V_o=3V[R_i=2k\Omega]T_a=25^\circ C$)

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Output saturation voltage	V_{sat}	$I_o=1A$, No L,D,Co	-	0.9	1.5	V
Reference voltage	V_{ref}	-	1.235	1.26	1.285	V
Temperature fluctuation in reference voltage	ΔV_{ref}	$T_j=0$ to $125^\circ C$	-	± 0.5	-	%
Load regulation	$ Reg _L$	$I_o=0.2$ to $1A$	-	0.1	1.5	%
Line regulation	$ Reg _I$	$V_{IN}=8$ to $35V$	-	0.5	2.5	%
Efficiency	η	$I_o=1A$	-	82	-	%
Oscillation frequency	f_o	-	80	100	120	kHz
Oscillation frequency temperature fluctuation	Δf_o	$T_j=0$ to $125^\circ C$	-	± 2	-	%
Maximum duty	D_{MAX}	④ terminal is open	90	-	-	%
Overcurrent detecting level	I_L	No L,D,Co	1.55	2.0	2.6	A
Charge current	I_{CHG}	②④ terminal is open	-15	-10	-5	μA
Input threshold voltage	V_{THL}	Duty=0%, ④ terminal=0V, ⑤ terminal	1.95	2.25	2.55	V
	V_{THH}	Duty= D_{MAX} , ④ terminal is open, ⑤ terminal	3.25	3.55	3.85	V
On threshold voltage	V_{THON}	④ terminal=0V, ⑤ terminal	1.05	1.4	1.75	V
Stand-by current	I_{SD}	$V_{IN}=40V$, ④ terminal=0V	-	150	400	μA
Output OFF-state consumption current	I_{qs}	$V_{IN}=40V$, ⑤ terminal=3V	-	8	12	mA

■ Block Diagram






Fig.1 Test Circuit




L : HK-14D100-2110 (made by Toho Co.)
 D : ERC80-004 (made by Fuji electronics Co.)

Fig.2 Power Dissipation vs. Ambient Temperature



Note) Oblique line portion : Overheat protection may operate in this area.

■ Step Down Type Circuit Diagram (5V output)**■ Polarity Inversion Type Circuit Diagram (-5V output)**