



N-Channel MOSFET

Features

- $R_{DS(on)}$ (Max 0.015 Ω) @ $V_{GS}=10V$
- Gate Charge (Typical 50nC)
- Improved dv/dt Capability, High Ruggedness
- 100% Avalanche Tested
- Maximum Junction Temperature Range (175°C)



General Description

This Power MOSFET is produced using Wisdom's advanced planar stripe, DMOS technology. This latest technology has been especially designed to minimize on-state resistance, have a high rugged avalanche characteristics. These devices are well suited for high efficiency switch mode power supplies, active power factor correction, electronic lamp ballasts based on half bridge topology.

Absolute Maximum Ratings

Symbol	Parameter	Value	Units
V_{DSS}	Drain to Source Voltage	60	V
I_D	Continuous Drain Current(@ $T_C = 25^\circ C$)	70	A
	Continuous Drain Current(@ $T_C = 100^\circ C$)	48	A
I_{DM}	Drain Current Pulsed (Note 1)	280	A
V_{GS}	Gate to Source Voltage	± 20	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	756	mJ
E_{AR}	Repetitive Avalanche Energy (Note 1)	16.2	mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)	7.0	V/ns
P_D	Total Power Dissipation(@ $T_C = 25^\circ C$)	162	W
	Derating Factor above 25 °C	1.08	W/°C
T_{STG}, T_J	Operating Junction Temperature & Storage Temperature	- 55 ~ 175	°C
T_L	Maximum Lead Temperature for soldering purpose, 1/8 from Case for 5 seconds.	300	°C

Thermal Characteristics

Symbol	Parameter	Value			Units
		Min.	Typ.	Max.	
R_{0JC}	Thermal Resistance, Junction-to-Case	-	-	0.93	°C/W
R_{0CS}	Thermal Resistance, Case to Sink	-	0.5	-	°C/W
R_{0JA}	Thermal Resistance, Junction-to-Ambient	-	-	62.5	°C/W

WFP70N06

Electrical Characteristics ($T_C = 25^\circ C$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	60	-	-	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature coefficient	$I_D = 250\mu A$, referenced to $25^\circ C$	-	0.07	-	V/ $^\circ C$
I_{DSS}	Drain-Source Leakage Current	$V_{DS} = 60V, V_{GS} = 0V$	-	-	10	μA
		$V_{DS} = 48V, T_C = 125^\circ C$	-	-	100	μA
I_{GSS}	Gate-Source Leakage, Forward	$V_{GS} = 20V, V_{DS} = 0V$	-	-	100	nA
	Gate-source Leakage, Reverse	$V_{GS} = -20V, V_{DS} = 0V$	-	-	-100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	-	4.0	V
$R_{DS(ON)}$	Static Drain-Source On-state Resistance	$V_{GS} = 10V, I_D = 35A$	-	0.0125	0.015	Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{GS} = 0V, V_{DS} = 25V, f = 1MHz$	-	1755	2280	pF
C_{oss}	Output Capacitance		-	790	1030	
C_{rss}	Reverse Transfer Capacitance		-	155	200	
Dynamic Characteristics						
$t_{d(on)}$	Turn-on Delay Time	$V_{DD} = 30V, I_D = 35A, R_G = 25\Omega$ (Note 4, 5)	-	25	60	ns
t_r	Rise Time		-	135	280	
$t_{d(off)}$	Turn-off Delay Time		-	115	240	
t_f	Fall Time		-	105	220	
Q_g	Total Gate Charge	$V_{DS} = 48V, V_{GS} = 10V, I_D = 70A$ (Note 4, 5)	-	50	65	nC
Q_{gs}	Gate-Source Charge		-	11	-	
Q_{gd}	Gate-Drain Charge(Miller Charge)		-	18	-	

Source-Drain Diode Ratings and Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit.
I_S	Continuous Source Current	Integral Reverse p-n Junction Diode in the MOSFET	-	-	70	A
I_{SM}	Pulsed Source Current		-	-	280	
V_{SD}	Diode Forward Voltage	$I_S = 70A, V_{GS} = 0V$	-	-	1.5	V
t_{rr}	Reverse Recovery Time	$I_S = 70A, V_{GS} = 0V, dI_F/dt = 100A/us$	-	60	-	ns
Q_{rr}	Reverse Recovery Charge		-	110	-	μC

* NOTES

1. Repetitive rating : pulse width limited by junction temperature
2. $L = 180\mu H, I_{AS} = 70A, V_{DD} = 25V, R_G = 25\Omega$, Starting $T_J = 25^\circ C$
3. $I_{SD} \leq 70A, di/dt \leq 300A/us, V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ C$
4. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$
5. Essentially independent of operating temperature.

Typical Characteristics




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

Typical Characteristics (Continued)




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On-Resistance Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature






Figure 11. Transient Thermal Response Curve


Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching Test Circuit & Waveforms



Peak Diode Recovery dv/dt Test Circuit & Waveforms



Package Dimensions

TO-220

