

HIGH FREQUENCY MAGNETICS

T1/E1 Through Hole Transformer

TM00119

- Designed for digital signaling interface applications to DS1 or DS1C cross connects (DSX)
- Operating Temperature Range: -40° C to +85° C
- Meets IEC 695, 2-2 flammability requirements
- PWB Process Capability: Standard Printed Wiring Board assembly techniques, total-immersion cleaning
- Reliability testing: Shock, vibration, temperature cycling, temperature - humidity - bias


ELECTRICAL SPECIFICATIONS AT 25° C

Part Number	Turns Ratio ±2%	Inductance ¹ mH Min	DCR Ω max		Leakage Inductance μH max	Interwinding Capacitance pF max	Minimum Interwinding Breakdown Voltage Vrms
	(3-1):(4-6)	(3-1)	(3-1)	(4-6)	(3-1)	(3-1) to (4-6)	
2745AG2	1:1CT	2.3	0.98	1.18	2.0	25	500

1. measured 10 kHz, 0.05 Vac

SCHEMATIC

2745AG2




HIGH FREQUENCY MAGNETICS

T1/E1 Through Hole Transformer

MECHANICAL

2745AG2



Unless otherwise specified, dimensions are nominal and in inches (millimeters).

©2000 Bel Fuse Inc. Specifications subject to change without notice. 09.00

CORPORATE

Bel Fuse Inc.
198 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

T1-44

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com