

## Long-life grade capacitors

### Applications


- Frequency converters

### Features

- Extended useful life, high reliability
- Good electrical characteristics and small dimensions
- Extremely high ripple current capability
- All-welded construction ensures reliable electrical contact
- Version with optimized construction for base cooling (2-pad solution) available
- Version with low-inductance design available
- Self-extinguishing electrolyt

### Construction


- Charge-discharge proof, polar
- Aluminum case with insulating sleeve
- Poles with screw terminal connections
- Mounting with ring clips, clamps or threaded stud
- The bases of types with threaded stud and  $d \leq 76,9$  mm are not insulated, types with  $d = 91$  mm have fully insulated bases



B43566

KAL0567-B

B43586


**Specifications and characteristics in brief**


Rated voltage $U_R$	350 ... 450 VDC		
Surge voltage $U_S$	$1,10 \cdot U_R$		
Rated capacitance $C_R$	470 ... 6 800 $\mu\text{F}$		
Capacitance tolerance	– 10/+ 30 % $\triangleq$ Q		
Leakage current $I_L$ (5 min, 20 °C)	$I_L \leq 0,3 \mu\text{A} \cdot \left(\frac{C_R}{\mu\text{F}} \cdot \frac{U_R}{V}\right)^{0,7} + 4 \mu\text{A}$		
Self-inductance $ESL$	$d = 51,6 \text{ mm}$ : approx. 15 nH $d = 76,9 \text{ mm}$ : approx. 20 nH $d = 91,0 \text{ mm}$ : approx. 20 nH Capacitors with low-inductance design: $d \geq 64,3 \text{ mm}$ : approx. 13 nH		
Useful life 85 °C; $U_R$ ; $I_{\sim R}$ 40 °C; $U_R$ ; $2 \cdot I_{\sim R}$	$> 24\,000 \text{ h}$ $> 250\,000 \text{ h}$	Requirements: $\Delta C/C \leq \pm 30\%$ of initial value $ESR \leq 3$ times initial specified limit $I_L \leq$ initial specified limit Failure percentage: $\leq 1\%$ Failure rate: $\leq 30 \text{ fit} (\leq 30 \cdot 10^{-9}/\text{h})$ (for definition "fit", refer to chapter "Quality", page 62)	
Voltage endurance test 85 °C; $U_R$ ; $I_{\sim R}$	5 000 h	Post test requirements: $\Delta C/C \leq \pm 10\%$ of initial value $ESR \leq 1,3$ times initial specified limit $I_L \leq$ initial specified limit	
Vibration resistance	To IEC 60068-2-6, test Fc: displacement amplitude 0,75 mm, frequency range 10 to 55 Hz, acceleration max. 10 g, duration $3 \times 2 \text{ h}$		
IEC climatic category	To IEC 60068-1: 350 VDC: 40/085/56 (– 40 °C/+ 85 °C/56 days damp heat test) <sup>1)</sup> $\geq 400 \text{ VDC}$ : 25/085/56 (– 25 °C/+ 85 °C/56 days damp heat test)		
Detail specifications	Similar to CECC 30301-803, CECC 30301-807		
Sectional specification	IEC 60384-4		

**Ripple current capability**

Due to the ripple current capability of the contact elements, the following current upper limits must not be exceeded:

Capacitor diameter	51,6 mm	64,3 mm	76,9 mm	91,0 mm
$I_{\sim \text{max}}$	30 A	40 A	50 A	70 A

1) For case dimensions 76,9 mm  $\times$  220,7 mm: IEC climatic category 25/085/56



B43566 / B43586

Extended Useful Life – 85 °C



### Dimensional drawings

#### Type B43566

Ring clip/clamp mounting

#### Type B43586

Threaded stud mounting



Positive pole marking: +

The base of all types with threaded stud and  $d = 91$  mm is fully insulated (the lengths  $l$  and  $l_1$  are increased by 0,5 mm in these cases). For types with threaded stud and  $d \leq 76$  mm the base is not insulated. Also refer to the notes on mounting given on page 168.

### Dimensions and weights


Ter- minal	Dimensions (mm) with insulating sleeve										Approx. wt. (g)
	$d$	$l \pm 1$	$l_1 \pm 1$	$l_2^{+0}_{-1}$	$l_3$	$d_1$	$d_2$ max	$d_3$ max	$a^{+0,2}_{-0,4}$		
M 5	51,6 $_{-0,8}^{+0}$	80,7	87,2	17	7,0 $_{-1}^{+0,2}$	M 12	8,2	13,5	22,2	220	
M 5	51,6 $_{-0,8}^{+0}$	105,7	112,2	17	7,0 $_{-1}^{+0,2}$	M 12	8,2	13,5	22,2	280	
M 5	64,3 $_{-0,8}^{+0}$	105,7	112,2	17	7,0 $_{-1}^{+0,2}$	M 12	8,2	13,5	28,5	440	
M 6	76,9 $_{-0,7}^{+0}$	105,7	111,5	17	6,4 $_{-0,8}^{+1,1}$	M 12	17,7	17,7	31,7	540	
M 6	76,9 $_{-0,7}^{+0}$	143,2	149,0	17	6,4 $_{-0,8}^{+1,1}$	M 12	17,7	17,7	31,7	840	
M 6	76,9 $_{-0,7}^{+0}$	220,7	226,5	17	6,4 $_{-0,8}^{+1,1}$	M 12	17,7	17,7	31,7	1300	
M 6	91,0 $_{-2}^{+0}$	144,5	149,8	17	6,4 $_{-0,8}^{+1,1}$	M 12	17,7	17,7	31,7	1200	

Dimensions are also valid for 2-pad solution and low-inductance design.

### Packing

For ecological reasons the packing is pure cardboard.


Capacitor diameter $d$	Packing units (pieces)
51,6 mm	22
64,3 mm	15
76,9 mm	12
91,0 mm	8



### Special designs

- Low-inductance design
- 2-pad solution

Design for optimized connection of the capacitor to the heatsink when using base cooling. This version is available for capacitors without threaded stud and for diameters  $\geq 64,3$  mm (cf.  $I_{-R}(B)$  in table “Technical data and ordering codes” and useful life graphs).



KAL0823-3-E

Ordering codes:

Design	Identification in 3rd block of ordering code	Remark
Low inductance (13 nH)	Q003	For capacitors with diameter $d \geq 64,3$ mm
2-pad solution	Q006	For capacitors with diameter $d \geq 64,3$ mm and without threaded stud

### Accessories

The following items are included in the delivery package, but are not fastened to the capacitors:

	Thread	Toothed washers	Screws/Nuts	Maximum torque
For terminals	M 5	A 5,1 DIN 6797	Cylinder-head screw M 5 $\times$ 8 DIN 84-4.8	2 Nm
	M 6	A 6,4 DIN 6797	Cylinder-head screw M 6 $\times$ 12 DIN 85-4.8	2,5 Nm
For mounting	M 12	J 12,5 DIN 6797	Hex nut BM 12 DIN 439	10 Nm

The following must be ordered separately:

Ring clips


 Clamps for capacitors with  $d \geq 64,3$  mm

Insulating parts

B44030 (cf. page 169)


B44030 (cf. page 173)

B44020 (cf. page 166)


**Overview of available types**

$U_R$ (VDC)	350	400	450
$C_R$ ( $\mu$ F)	Case dimensions $d \times l$ (mm)		
470		51,6 × 80,7	51,6 × 80,7
680	51,6 × 80,7	51,6 × 80,7	51,6 × 105,7
1 000	51,6 × 80,7	51,6 × 105,7	64,3 × 105,7
1 500	51,6 × 105,7	64,3 × 105,7	76,9 × 105,7
2 200	64,3 × 105,7	76,9 × 105,7	76,9 × 143,2
2 700			91,0 × 144,5
3 300	76,9 × 105,7	76,9 × 143,2	76,9 × 220,7
4 700	76,9 × 143,2	76,9 × 220,7 91,0 × 144,5	
6 000	76,9 × 220,7 91,0 × 144,5	76,9 × 220,7	
6 800	76,9 × 220,7		


The capacitance and voltage ratings listed above are available in different cases upon request. Other voltage and capacitance ratings are also available upon request.


**Technical data and ordering codes**

$U_R$	$C_R$	Case dimensions	$ESR_{max}$	$Z_{max}$	$I_{\sim max}$	$I_{\sim max}$	$I_{\sim R}$	$I_{\sim R(B)}$	Ordering code <sup>1)</sup>
VDC	100 Hz 20 °C $\mu F$	$d \times l$ mm	100 Hz 20 °C m $\Omega$	10 kHz 20 °C m $\Omega$	100 Hz 40 °C A	100 Hz 85 °C A	100 Hz 85 °C A	100 Hz 85 °C A	
350	680	51,6 × 80,7	120	100	13	5,0	4,4	8,0	B435*6A4687Q000
	1 000	51,6 × 80,7	84	73	16	6,3	5,6	12	B435*6B4108Q000
	1 500	51,6 × 105,7	59	52	21	8,3	7,3	14	B435*6B4158Q000
	2 200	64,3 × 105,7	43	39	28	11	9,4	17	B435*6A4228Q000 <sup>2)</sup>
	3 300	76,9 × 105,7	32	29	33	13	12	21	B435*6A4338Q000 <sup>2)</sup>
	4 700	76,9 × 143,2	25	23	44	17	15	27	B435*6A4478Q000 <sup>2)</sup>
	6 000	76,9 × 220,7	22	21	50	20	18	25	B435*6B4608Q000 <sup>2)</sup>
	6 000	91,0 × 144,5	23	22	51	20	18	32	B435*6J4608Q000 <sup>2)</sup>
400	6 800	76,9 × 220,7	20	19	50	22	19	28	B435*6B4688Q000 <sup>2)</sup>
	470	51,6 × 80,7	325	290	10	4,0	3,5	6,2	B435*6A0477Q000
	680	51,6 × 80,7	225	200	13	5,1	4,5	9,0	B435*6A0687Q000
	1 000	51,6 × 105,7	160	140	17	6,6	5,8	11	B435*6A0108Q000
	1 500	64,3 × 105,7	100	92	22	8,5	7,5	13	B435*6A0158Q000 <sup>2)</sup>
	2 200	76,9 × 105,7	83	65	29	11	9,9	19	B435*6A0228Q000 <sup>2)</sup>
	3 300	76,9 × 143,2	58	47	38	15	13	23	B435*6A0338Q000 <sup>2)</sup>
	4 700	76,9 × 220,7	43	40	50	19	17	24	B435*6A0478Q000 <sup>2)</sup>
450	4 700	91,0 × 144,5	38	40	53	21	18	34	B435*6J0478Q000 <sup>2)</sup>
	6 000	76,9 × 220,7	35	33	50	24	21	31	B435*6A0608Q000 <sup>2)</sup>
	470	51,6 × 80,7	350	310	11	4,2	3,7	7,4	B435*6A5477Q000
	680	51,6 × 105,7	250	220	14	5,4	4,8	8,6	B435*6A5687Q000
	1 000	64,3 × 105,7	190	173	17	6,7	6,0	11	B435*6A5108Q000 <sup>2)</sup>
	1 500	76,9 × 105,7	125	120	24	9,3	8,2	16	B435*6A5158Q000 <sup>2)</sup>
	2 200	76,9 × 143,2	95	90	30	12	10	17	B435*6A5228Q000 <sup>2)</sup>
	2 700	91,0 × 144,5	75	83	36	14	12	21	B435*6A5278Q000 <sup>2)</sup>
3 300	76,9 × 220,7	70	67	40	15	14	19	B435*6A5338Q000 <sup>2)</sup>	

1) \* "6" = for capacitors with ring clip/clamp mounting  
"8" = for capacitors with threaded stud

2) For 2-pad solution (types without threaded stud) and for low-inductance design, see page 145.




**B43566 / B43586**


**Extended Useful Life – 85 °C**

**Useful life**

depending on ambient temperature  $T_A$  (for natural cooling) and versus temperature of case base  $T_B$  (for base cooling) under ripple current operating conditions<sup>1)</sup>




**Frequency factor of permissible ripple current  $I_{\sim}$  versus frequency  $f$**




$d$ (mm)	51,6	64,3	76,9	91,0
Curve	c	b	a	c

1) The ripple current refers to  $I_{\sim R}$  for natural cooling or to  $I_{\sim R(B)}$  for base cooling, respectively. Refer to page 40 for an explanation on how to interpret the useful life graphs.



**Frequency characteristics of ESR**  
Typical behavior



$d$ (mm)	51,6	64,3	76,9	91,0
Curve	c	b	a	a



**Herausgegeben von EPCOS AG**

**Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND**

**☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

**Published by EPCOS AG**

**Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY**

**☎ ++49 89 636 09, FAX (0 89) 636-2 26 89**

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.