


MBN400GR12

[Rated 400A/1200V, Single-pack type]


FEATURES

- Low saturation voltage and high speed.
- Low turn-OFF switching loss.
- Low noise due to build-in free-wheeling diode.
(Ultra Soft and Fast recovery Diode (USFD))
- High reliability structure.
- Isolated heat sink (terminals to base).

CIRCUIT DIAGRAM



OUTLINE DRAWING



ABSOLUTE MAXIMUM RATINGS($T_c=25^\circ\text{C}$)

Item	Symbol	Unit	Value	
Collector-Emitter Voltage	V_{CES}	V	1200	
Gate-Emitter Voltage	V_{GES}	V	± 20	
Collector Current	DC	I_C	400	
	1ms	I_{CP}	800	
Forward Current	DC	I_F	400 ^{*1}	
	1ms	I_{FM}	800	
Collector Power Dissipation	P_C	W	2080	
Junction Temperature	T_j	$^\circ\text{C}$	-40 ~ +150	
Storage Temperature	T_{stg}	$^\circ\text{C}$	-40 ~ +125	
Isolation Voltage	V_{iso}	V_{RMS}	2500(AC 1 minute)	
Screw Torque	Terminals (M4/M6)	-	N·m (kgf·cm)	1.37(14) / 2.94(30) ^{*2}
	Mounting			2.94(30) ^{*3}

Notes; *1: RMS current of Diode ≤ 120 Arms

*2: Recommended value 1.18 / 2.45 N·m (12 / 25 kgf·cm)







*3: Recommended value 2.45 N·m (25 kgf·cm)


CHARACTERISTICS ($T_c=25^\circ\text{C}$)

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions	
Collector-Emitter Cut-Off Current	I_{CES}	mA	-	-	1.0	$V_{CE}=1200\text{V}$, $V_{GE}=0\text{V}$	
Gate-Emitter Leakage Current	I_{GES}	nA	-	-	± 500	$V_{GE}=\pm 20\text{V}$, $V_{CE}=0\text{V}$	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V	-	2.2	2.8	$I_C=400\text{A}$, $V_{GE}=15\text{V}$	
Gate-Emitter Threshold Voltage	$V_{GE(TH)}$	V	-	-	10	$V_{CE}=5\text{V}$, $I_C=400\text{mA}$	
Input Capacitance	C_{ies}	pF	-	37000	-	$V_{CE}=10\text{V}$, $V_{GE}=0\text{V}$, $f=1\text{MHz}$	
Switching Times	Rise Time	t_r	-	0.25	0.7	$V_{CC}=600\text{V}$ $R_L=1.5\Omega$ $R_G=2.7\Omega$ ^{*4} $V_{GE}=\pm 15\text{V}$	
	Turn-ON Time	t_{on}	-	0.4	0.9		
	Fall Time	t_f	-	0.2	0.35		
	Turn-Off Time	t_{off}	-	0.7	1.1		
Peak Forward Voltage Drop	V_{FM}	V	-	2.5	3.5	$I_F=400\text{A}$, $V_{GE}=0\text{V}$	
Reverse Recovery Time	t_{rr}	μs	-	-	0.4	$I_F=400\text{A}$, $V_{GE}=-10\text{V}$, $di/dt=400\text{A}/\mu\text{s}$	
Thermal Impedance	IGBT	$R_{th(j-c)}$	$^\circ\text{C/W}$	-	-	0.06	Junction to case
	FWD	$R_{th(j-c)}$				0.10	


Notes; *4: R_G value is the test condition's value for decision of the switching times, not recommended value, please determine the suitable R_G value after the measurement of switching waveforms (overshoot voltage, etc.) with appliance mounted.

Remark; The specification given herein, is subject to change without prior notice to improve product characteristics.







Switching time vs. Collector current





Switching time vs. Gate resistance



Switching loss vs. Collector current



Switching loss vs. Gate resistance



HITACHI POWER SEMICONDUCTORS

Notices

- 1.The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact Hitachi sales department for the latest version of this data sheets.
- 2.Please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
- 3.In cases where extremely high reliability is required(such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult Hitachi's sales department staff.
- 4.In no event shall Hitachi be liable for any damages that may result from an accident or any other cause during operation of the user's units according to this data sheets. Hitachi assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in this data sheets.
- 5.In no event shall Hitachi be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 6.No license is granted by this data sheets under any patents or other rights of any third party or Hitachi, Ltd.
- 7.This data sheets may not be reproduced or duplicated, in any form, in whole or in part , without the expressed written permission of Hitachi, Ltd.
- 8.The products (technologies) described in this data sheets are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety not are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

-
- For inquiries relating to the products, please contact nearest overseas representatives which is located "Inquiry" portion on the top page of a home page.
-

Hitachi power semiconductor home page address <http://www.hitachi.co.jp/pse>

HITACHI