

SIDE LOOK PACKAGE

NPN PHOTODETECTOR


MID-11A22

Description

The MID-11A22 is a NPN silicon phototransistor mounted in a lensed , special dark plastic and side looking package.

Package Dimensions

Unit: mm (inches)



Features

- Wide range of collector current
- Lensed for high sensitivity
- Low cost plastic package
- Good spectral matching to IRED (λ_p 940 nm) type.

Notes :

1. Tolerance for excess molding compound is ± 0.005 ".
2. Lead spacing is measured where the leads emerge from the

Absolute Maximum Ratings

@ $T_A=25^{\circ}\text{C}$

Parameter	Maximum Rating	Unit
Power Dissipation	100	mW
Collector-Emitter Voltage	30	V
Emitter-Collector Voltage	5	V
Operating Temperature Range	-55°C to $+100^{\circ}\text{C}$	
Storage Temperature Range	-55°C to $+100^{\circ}\text{C}$	
Lead Soldering Temperature	260°C for 5 seconds	

UNi

Unity Opto Technology Co., Ltd.

02/04/2002

Optical-Electrical Characteristics

@ $T_A=25^{\circ}\text{C}$

Parameter	Test Conditions	Symbol	Min.	Typ .	Max.	Unit
Collector-Emitter Breakdown Voltage	$I_c=0.1\text{mA}$ $E_e=0$	$V_{(BR)CEO}$	30			V
Emitter-Collector Breakdown Voltage	$I_e=0.1\text{mA}$ $E_e=0$	$V_{(BR)ECO}$	5			V
Collector-Emitter Saturation Voltage	$I_c=0.5\text{mA}$ $E_e=0.1\text{mW/cm}^2$	$V_{CE(SAT)}$			0.4	V
Rise Time	$V_R=30\text{V}$, $0=1\text{K}\Omega$	T_r		15		μS
Fall Time	$I_C=1\text{mA}$	T_f		15		
Collector Dark Current	$V_{CE}=10\text{V}$ $E_e=0$	I_{CEO}			100	nA
On State Collector Current	$V_{CE}=5\text{V}$ $E_e=0.1\text{mW/cm}^2$	$I_{C(ON)}$		0.38		mA

Typical Optical-Electrical Characteristic Curves




FIG.1 COLLECTOR DARK CURRENT VS AMBIENT TEMPERATURE




FIG.2 NORMALIZED COLLECTOR CURRENT VS AMBIENT TEMPERATURE




FIG.3 RISE AND FALL TIME VS LOAD RESISTANCE




FIG.4 RELATIVE COLLECTOR CURRENT VS IRRADIANCE




FIG.5 SENSITIVITY DIAGRAM