


1.2V / 2.5V Micropower Voltage Reference

FEATURES

- Initial Voltage Tolerance:
 SPX1004-1.2 = $\pm 10\text{mV}$
 SPX1004-2.5 = $\pm 20\text{mV}$
- Low Dynamic Impedance
 0.6 Ω Max.
- Low Operating Current:
 SPX1004-1.2 = $\pm 10\mu\text{A}$
 SPX1004-2.5 $\pm 20\mu\text{A}$
- Wide Operating Current Range
 0.6 Ω Max.
- Direct Replacement for LT1004,
 LM1004 and AS1004
- Lead Free, RoHS Compliant
 Packages



APPLICATIONS

- A/D and D/A Reference
- Reference for 5V Systems
- Digital Voltmeter
- Power Supply Monitor

DESCRIPTION

The SPX1004 is a 2-terminal bandgap precision voltage reference that provides a stable fixed output voltage of 1.2V and 2.5V with a tolerance of $\pm 10\text{mV}$ for SPX1004-1.2 and $\pm 20\text{mV}$ for SPX1004-2.5. Design, process and precision on chip trimming yield a very low temperature coefficient of 25 ppm/ $^{\circ}\text{C}$.

The SPX1004 can be used as a pin-to-pin replacement for the LT1004, LM1004 or AS1004. The SPX1004 is available in SOT-89, NSOIC-8 and TO-92 packages over the operating temperature range of 0°C to 70°C .

BLOCK DIAGRAMS




Figure 1a. SPX1004-1.2 Block Diagram




Figure 1b. SPX1004-2.5 Block Diagram

ABSOLUTE MAXIMUM RATINGS

Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

| | |
|---|-----------------|
| Forward Current (I_{AK})..... | 10mA |
| Reverse Current (I_{KA})..... | 30mA |
| Lead Temperature (soldering, 10 seconds)..... | 300°C |
| Storage Temperature Range..... | -65°C to +150°C |
| Junction Temperature..... | 150°C |

Continuous Power Dissipation (P_D)

| | |
|--------------|--------|
| TO-92..... | 775mW |
| NSOIC-8..... | 750mW |
| SOT-89..... | 1000mW |

TYPICAL THERMAL RESISTANCES

| PACKAGE | θ_{JA} | θ_{JA} | TYPICAL DERATING |
|---------|---------------|---------------|------------------|
| TO-92 | 160°C/W | 80°C/W | 6.3 mW/°C |
| NSOIC-8 | 175°C/W | 45°C/W | 5.7mW/°C |
| SOT-89 | 110°C/W | 8°C/W | 9.1mW/°C |

ELECTRICAL CHARACTERISTICS

Electrical characteristics are guaranteed over full junction temperature range (0°C to 70°C). Ambient temperature must be derated based on power dissipation and package thermal characteristics.

| PARAMETER | CONDITIONS | SPX1004-1.2V | | | SPX1004-2.5V | | | UNITS |
|---|---|--------------------------------------|-------|-------|--------------------------------------|-------|-------|-------------|
| | | MIN | TYP | MAX | MIN | TYP | MAX | |
| Reverse breakdown | $I_Z=100\mu A$, $T_J=25^\circ C$ $0^\circ C \leq T_A \leq 70^\circ C$ | 1.225 | 1.235 | 1.245 | 2.480 | 2.500 | 2.520 | V |
| Ave Temp. Coeff. | $I_{min} \leq I_Z \leq 20mA$ | 20 | | | 60 | | | ppm/ °C |
| Min Operating Current | | 4 10 | | | 12 20 | | | μA |
| Reverse Breakdown Voltage Change with Current | $I_{min} \leq I_Z \leq 1mA$ over temperature $1mA \leq I_Z \leq 20mA$ over temperature | 0.5 1 0.5 1.5 6.5 10 6.5 20 | | | 0.5 1 0.5 1.5 6.5 10 6.5 20 | | | mV |
| Reverse Dynamic Impedance | $I_Z=100\mu A$, $f=25Hz$ over temperature | 0.2 0.6 1 1.5 | | | 0.8 0.9 1.5 | | | Ω |
| Wide Band Noise | $I_Z=100\mu A$, $10Hz \leq f \leq 10kHz$ | 60 | | | 120 | | | μV |
| Long Term Stability | $I_Z=100\mu A$, $T_A=25^\circ C \pm 0.1^\circ C$ | 20 | | | 60 | | | ppm/ kHr |
| Operating Temp Range | | 0 70 | | | 0 70 | | | °C |




Figure 2. V_{REF} vs Temperature for 2.5V Version

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 3. SPX1004-1.2V Reverse Operating Characteristic




Figure 4. SPX1004-2.5V Reverse Operating Characteristic




Figure 5. SPX1004-1.2V Reverse Dynamic Impedance




Figure 6. SPX1004-2.5V Reverse Dynamic Impedance




Figure 7. Forward Characteristics for SPX1004-1.2 and SPX1004-2.5




Figure 8. Low Frequency Reverse Dynamic Impedance for SPX1004-1.2




Figure 9a. 1.2V Reference, Figure 9b. 2.5V Reference




Figure 10. Low Noise Reference




Figure 11. Variable Output Regulator




Figure 12. High Stability 5V Regulator




Figure 13. Low Battery Detector






Figure 14. Micropower 10V Reference


PACKAGE: PINOUTS




PACKAGE: 3 PIN SOT-89




| REVISION HISTORY | | | |
|------------------|-----------------------------|----------|-------|
| REV. | DISCRIPTION | DATE | APP'D |
| A | DRAWING ORIGINATION | 08/16/05 | JL |
| B | DRAWING FORMAT MODIFICATION | 07/19/08 | JL |



Top View





Side View



Front View

| 8 Pin SOICN | | JEDEC MS-012 | | Variation AA | | |
|-------------|------------------------------------|--------------|------|--|-----|-------|
| SYMBOLS | DIMENSIONS IN MM (Control Unit) | | | DIMENSIONS IN INCH (Reference Unit) | | |
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | 1.35 | — | 1.75 | 0.053 | — | 0.069 |
| A1 | 0.10 | — | 0.25 | 0.004 | — | 0.010 |
| A2 | 1.25 | — | 1.65 | 0.049 | — | 0.065 |
| b | 0.31 | — | 0.51 | 0.012 | — | 0.020 |
| c | 0.17 | — | 0.25 | 0.007 | — | 0.010 |
| E | 6.00 BSC | | | 0.236 BSC | | |
| E1 | 3.90 BSC | | | 0.154 BSC | | |
| e | 0.25 | — | 0.50 | 0.010 | — | 0.020 |
| L | 0.40 | — | 1.27 | 0.016 | — | 0.050 |
| L1 | 1.04 REF | | | 0.041 REF | | |
| L2 | 0.25 BSC | | | 0.010 BSC | | |
| R | 0.07 | — | — | 0.003 | — | — |
| R1 | 0.07 | — | — | 0.003 | — | — |
| θ | 0° | — | 8° | 0° | — | 8° |
| $\theta 1$ | 5° | — | 15° | 5° | — | 15° |
| $\theta 2$ | 0° | — | — | 0° | — | — |
| D | 4.90 BSC | | | 0.193 BSC | | |
| N | 8 | | | 8 | | |

| | | | |
|---|----------------|---------------------------|---------------|
|  | | SIPLEX CORPORATION | |
| | | | |
| By: JL | Date: 07/19/06 | Revision: B | Sheet: 1 OF 1 |



ORDERING INFORMATION

| Part Number | Accuracy | Output Voltage | MSL Level | RoHS | Package | Pack Type | Quantity |
|---------------------|----------|----------------|-------------------------------|------|-----------------------|-------------|----------|
| SPX1004AS1-L-1-2 | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 | TUBE | 98 |
| SPX1004AS1-L-1-2/TR | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 | Tape & Reel | 2500 |
| SPX1004AS2-L-1-2 | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004AS2-L-1-2/TR | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 | Tape & Reel | 2500 |
| SPX1004S1-L-1-2 | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 | TUBE | 98 |
| SPX1004S1-L-1-2/TR | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 | Tape & Reel | 2500 |
| SPX1004S2-L-1-2 | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004S2-L-1-2/TR | 0.8% | 1.235V | L1 @ 260°C | Yes | NSOIC8 Alt. Pinout | Tape & Reel | 2500 |
| SPX1004AM1-L-1-2 | 0.8% | 1.235V | L2 @ 260°C | Yes | SOT-89-3 | Canister | Any |
| SPX1004AM1-L-1-2/TR | 0.8% | 1.235V | L2 @ 260°C | Yes | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004M-L-1-2 | 0.8% | 1.235V | L2 @ 260°C | Yes | SOT-89-3 | Canister | Any |
| SPX1004M-L-1-2/TR | 0.8% | 1.235V | L2 @ 260°C | Yes | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004AN-L-1-2 | 0.8% | 1.235V | No MSL for thru hole package. | Yes | TO-92-3 | BOX | Any |
| SPX1004AN-L-1-2/TR | 0.8% | 1.235V | No MSL for thru hole package. | Yes | TO-92-3 | Tape & Reel | 2000 |
| SPX1004N-L-1-2 | 0.8% | 1.235V | No MSL for thru hole package. | Yes | TO-92-3 | BOX | Any |
| SPX1004N-L-1-2/TR | 0.8% | 1.235V | No MSL for thru hole package. | Yes | TO-92-3 | Tape & Reel | 2000 |
| SPX1004AS1-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 | TUBE | 98 |
| SPX1004AS1-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 | Tape & Reel | 2500 |
| SPX1004AS2-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004AS2-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | Tape & Reel | 2500 |
| SPX1004S1-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 | TUBE | 98 |
| SPX1004S1-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 | Tape & Reel | 2500 |
| SPX1004S2-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004S2-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | Tape & Reel | 2500 |
| SPX1004AM1-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Canister | Any |
| SPX1004AM1-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004M1-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Canister | Any |
| SPX1004M1-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004M-1-2 | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Canister | Any |
| SPX1004M-1-2/TR | 0.8% | 1.235V | L1 @ 240°C | No | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004AN-1-2 | 0.8% | 1.235V | No MSL for thru hole package. | No | TO-92-3 | BOX | Any |
| SPX1004AN-1-2/TR | 0.8% | 1.235V | No MSL for thru hole package. | No | TO-92-3 | Tape & Reel | 2000 |
| SPX1004N-1-2 | 0.8% | 1.235V | No MSL for thru hole package. | No | TO-92-3 | BOX | Any |
| SPX1004N-1-2/TR | 0.8% | 1.235V | No MSL for thru hole package. | No | TO-92-3 | Tape & Reel | 2000 |

ORDERING INFORMATION (continued)

| Part Number | Accuracy | Output Voltage | MSL Level | RoHS | Package | Pack Type | Quantity |
|--------------------|----------|----------------|-------------------------------|------|-----------------------|-------------|----------|
| SPX1004S1-L-2-5 | 0.8% | 2.500V | L1 @ 260°C | Yes | NSOIC8 | TUBE | 98 |
| SPX1004S1-L-2-5/TR | 0.8% | 2.500V | L1 @ 260°C | Yes | NSOIC8 | Tape & Reel | 2500 |
| SPX1004S2-L-2-5 | 0.8% | 2.500V | L1 @ 260°C | Yes | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004S2-L-2-5/TR | 0.8% | 2.500V | L1 @ 260°C | Yes | NSOIC8 Alt. Pinout | Tape & Reel | 2500 |
| SPX1004M1-L-2-5 | 0.8% | 2.500V | L2 @ 260°C | Yes | SOT-89-3 | Canister | Any |
| SPX1004M1-L-2-5/TR | 0.8% | 2.500V | L2 @ 260°C | Yes | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004M-L-2-5 | 0.8% | 2.500V | L2 @ 260°C | Yes | SOT-89-3 | Canister | Any |
| SPX1004M-L-2-5/TR | 0.8% | 2.500V | L2 @ 260°C | Yes | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004N-L-2-5 | 0.8% | 2.500V | No MSL for thru hole package. | Yes | TO-92-3 | BOX | Any |
| SPX1004N-L-2-5/TR | 0.8% | 2.500V | No MSL for thru hole package. | Yes | TO-92-3 | Tape & Reel | 2000 |
| SPX1004S1-2-5 | 0.8% | 2.500V | L1 @ 240°C | No | NSOIC8 | TUBE | 98 |
| SPX1004S1-2-5/TR | 0.8% | 2.500V | L1 @ 240°C | No | NSOIC8 | Tape & Reel | 2500 |
| SPX1004S2-2-5 | 0.8% | 2.500V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | TUBE | 98 |
| SPX1004S2-2-5/TR | 0.8% | 2.500V | L1 @ 240°C | No | NSOIC8 Alt. Pinout | Tape & Reel | 2500 |
| SPX1004M1-2-5 | 0.8% | 2.500V | L1 @ 240°C | No | SOT-89-3 | Canister | Any |
| SPX1004M1-2-5/TR | 0.8% | 2.500V | L1 @ 240°C | No | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004M-2-5 | 0.8% | 2.500V | L1 @ 240°C | No | SOT-89-3 | Canister | Any |
| SPX1004M-2-5/TR | 0.8% | 2.500V | L1 @ 240°C | No | SOT-89-3 | Tape & Reel | 2500 |
| SPX1004N-2-5 | 0.8% | 2.500V | No MSL for thru hole package. | No | TO-92-3 | BOX | Any |
| SPX1004N-2-5/TR | 0.8% | 2.500V | No MSL for thru hole package. | No | TO-92-3 | Tape & Reel | 2000 |

For latest information on ordering status, go to the Sipex Web Landing Page for this product
<http://www.sipex.com/searchResults.aspx?keywordsval=spx1004>

For further assistance:

Email: Sipexsupport@sipex.com
 WWW Support page: <http://www.sipex.com/content.aspx?p=support>
 Sipex Application Notes: <http://www.sipex.com/applicationNotes.aspx>



Sipex Corporation
 Headquarters and
 Sales Office
 233 South Hillview Drive
 Milpitas, CA 95035
 tel: (408) 934-7500
 fax: (408) 935-7600

Sipex Corporation reserves the right to make changes to any products described herein. Sipex does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others.