

**VI TELEFILTER****Filter Specification****TFS 36 F****1/5****Description**

IF filter for digital cable TV

**Measurement condition**

Ambient temperature  $T_A$ : 25 °C  
 Input power level: 0 dBm  
 Terminating impedance: source: 50  $\Omega$   
 load: 2 k $\Omega$  || 3 pF

**Characteristics**

Remark:

Reference level for the relative attenuation  $a_{rel}$  of the TFS 36F is the insertion loss. The insertion loss  $a_0$  is defined as the insertion loss at the nominal frequency  $f_N$ .

D a t a		typ. Value		Limit		
<b>Insertion loss</b> (reference level)		19,6	MHz	20,3	$\pm$ 1,5	dB
<b>Nominal frequency</b> $f_N$		-				36,125 MHz
<b>Centre frequency</b> $f_C$ at ambient temperature $T_A$		-				36,125 MHz $\pm$ 0,055 MHz
<b>Bandwidth</b>	1 dB	7,5	MHz			-
	3 dB	7,9	MHz			-
	30 dB	9,3	MHz			-
<b>Group delay ripple</b>	p-p in $f_C \pm 3,75$ MHz	40	ns			-
<b>Relative attenuation</b> $a_{rel}$						
	32,32 MHz	1,6	dB			-
	39,93 MHz	1,2	dB	1,1	$\pm$ 1	dB
	32,13 MHz	3,8	dB	3,1	$\pm$ 1,2	dB
	40,13 MHz	3,4	dB	3,2	$\pm$ 1,2	dB
	31,25 MHz	41	dB	min.		35 dB
	47,25 MHz	47	dB	min.		42 dB
lower side lobe	25,00 ... 29,50 MHz	42	dB	min.		36 dB
	29,50 ... 31,25 MHz	39	dB	min.		32 dB
upper side lobe	40,90 ... 43,50 MHz	35	dB	min.		32 dB
	43,50 ... 50,00 MHz	41	dB	min.		36 dB
<b>Reflected wave signal suppression</b> 1,2 $\mu$ s...6,0 $\mu$ s after main pulse		55	dB	min.		42 dB
<b>Feedthrough signal suppression</b>		53	dB	min.		50 dB
<b>Operable temperature range</b>		-		-25 ...		65 °C
<b>Storage temperature range</b>		-		-40 ...		85 °C
<b>Temperature coefficient of frequency</b> $TC_f^*$		- 0,072	ppm / K			-

\*)  $\Delta f_C(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_A) \times f_{CAT}(\text{MHz})$ 

generated: \_\_\_\_\_


checked / approved: \_\_\_\_\_

TELEFILTER GmbH  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [fft@telefilter.com](mailto:fft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**Construction and pin connection**

(all dimensions in mm)



1	input
2	input - ground
3	chip carrier - ground
4	output
5	output
6,7,8	internally connected to pin 3

date code:	year + week
N	2001
P	2002
R	2003
...	

**TELEFILTER GmbH**  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

---

**VI TELEFILTER****Filter Specification****TFS 36 F****3/5**

---

**Stability Characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;  
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;  
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles  
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;  
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;

**Packing**

- Tape & Reel: DIN IEC 286 – 3, with exception of value for N and minimum bending radius;  
tape type II, embossed carrier tape with top cover tape on the upper side;

---

**TELEFILTER GmbH**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@tefilter.com](mailto:tft@tefilter.com)**

---

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**VI TELEFILTER****Filter Specification****TFS 36 F****4/5****Air reflow temperature conditions**1<sup>st</sup> and 2<sup>nd</sup> air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C – 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. – 90 sec.	20 sec. – 25 sec.	


**Chip-mount air reflow profile**

Table for temperature vs. Time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	Temperature / °C	time / sec.	Temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

TELEFILTER GmbH  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**VI TELEFILTER****Filter Specification****TFS 36 F****5/5****History**

<b>Version</b>	<b>Reason of Changes</b>	<b>Name</b>	<b>Date</b>
1.0	generate specification	Pfeiffer	01.08.2002
1.1	change package	Pfeiffer	29.11.2002
1.2	add typical values	Pfeiffer	07.02.2003

---

**TELEFILTER GmbH**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@tefilter.com](mailto:tft@tefilter.com)**

---

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.