


ZNI1000

TEMPERATURE SENSOR

DESCRIPTION

The ZNI1000 is a Ni thin film Resistance Temperature Detector (RTD), specified to DIN 43760. The high temperature coefficient offers higher signal outputs than other RTD's, which results in higher accuracy with smaller temperature changes.



SOT23

FEATURES

- Resistance at 0°C: 1000Ω
- SOT23 package
- Available on 8mm tape

APPLICATIONS

- Automotive Electronic
- Circuit Protection
- Temperature compensation
- Temperature measurement


ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZNI1000TA	7"	8mm	3000 units
ZNI1000TC	13"	8mm	10000 units

DEVICE MARKING

- ZNI

PINOUT



Top View

Pin 1 - Ni1000
Pin 2 - Ni1000
Pin 3 - need a good thermal contact for a short response time

ZNI1000

ABSOLUTE MAXIMUM RATINGS.


PARAMETER	SYMBOL	LIMIT	UNIT
Continuous Current	I_{CC}	4	mA
Total power dissipation	P_{TOT}	20	mW
Operating Temperature Range	T_{amb}	-55 to +150	°C
Storage Temperature Range	T_{stg}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Resistance 0°C	R_0	-	1000	-	Ω	$T=0^\circ\text{C}$, $I<1\text{mA}$
Resistance 100°C	R_{100}	-	1618	-	Ω	$T=100^\circ\text{C}$, $I<1\text{mA}$
Tolerance Class B		-	$\pm(0.4+0.028 \times T)$	-		-55 to 0°C
Tolerance Class B		-	$\pm(0.4+0.007 \times T)$	-		0 to 150°C


CHARACTERISTICS ACCORDING TO DIN43760

R_0 Resistance at 0°C B 6.650×10^{-6}
 T Temperature in °C C 2.805×10^{-11}
 A 5.485×10^{-3} D -2.000×10^{-17}
 $R(T) = R_0 \times (1 + A \times T + B \times T^2 + C \times T^4 + D \times T^6)$




ZNI1000

PACKAGE OUTLINE



PAD LAYOUT



CONTROLLING DIMENSIONS IN MILLIMETRES APPROX CONVERSIONS INCHES.

PACKAGE DIMENSIONS

DIM	MILLIMETRES		INCHES		DIM	MILLIMETRES		INCHES	
	MIN	MAX	MIN	MAX		MIN	MAX	MIN	MAX
A	2.67	3.05	0.105	0.120	H	0.33	0.51	0.013	0.020
B	1.20	1.40	0.047	0.055	K	0.01	0.10	0.0004	0.004
C	—	1.10	—	0.043	L	2.10	2.50	0.083	0.0985
D	0.37	0.53	0.015	0.021	M	0.45	0.64	0.018	0.025
F	0.085	0.15	0.0034	0.0059	N	0.95 NOM		0.0375 NOM	
G	1.90 NOM		0.075 NOM		φ	10° TYP		10° TYP	

© Zetex plc 2002

Europe

Zetex plc
Fields New Road
Chadderton
Oldham, OL9 8NP
United Kingdom
Telephone (44) 161 622 4422
Fax: (44) 161 622 4420
uk.sales@zetex.com

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49
europe.sales@zetex.com

Americas

Zetex Inc
700 Veterans Memorial Hwy
Hauppauge, NY11788
USA
Telephone: (631) 360 2222
Fax: (631) 360 8222
usa.sales@zetex.com

Asia Pacific

Zetex (Asia) Ltd
3701-04 Metroplaza, Tower 1
Hing Fong Road
Kwai Fong
Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494
asia.sales@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com

ISSUE 1 - AUGUST 2002

