


Features

- Dual TVS in Common Cathode Configuration for ESD Protection
- 40 Watt Peak Power Dissipation @ 1.0ms (Unidirectional)
- 225 mW Power Dissipation
- Ideally Suited for Automatic Insertion
- Low Leakage
- Lead Free/RoHS Compliant (Note 4)
- Qualified to AEC-Q101 Standards for High Reliability

Mechanical Data

- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Rating Classification 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Polarity: See Diagram
- Date Code: See Page 3
- Marking Code: See Table Below
- Weight: 0.008 grams (approximate)



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
	0	8
All Dimensions in mm		

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 1)	P _d	225	mW
Peak Power Dissipation (Note 2)	P _{PK}	40	W
Thermal Resistance, Junction to Ambient Air (Note 1)	R _{JA}	556	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

V_F = 0.9V max @ I_F = 10mA (Note 3)

Type Number	Marking Code	V _{RWM}	I _R @ V _{RWM}	Breakdown Voltage			V _C @ I _{PP} (Note 2)		Typical Temperature Coefficient	
				V _{BR} (Note 3) (V)			@ I _T	V _C		I _{PP}
				Volts	nA	Min	Nom	Max	mA	V
MMBZ15VDL	KVJ	12.8	100	14.3	15	15.8	1.0	21.2	1.9	+0.080

V_F = 1.1V max @ I_F = 200mA (Note 3)

Type Number	Marking Code	V _{RWM}	I _R @ V _{RWM}	Breakdown Voltage			V _C @ I _{PP} (Note 2)		Typical Temperature Coefficient	
				V _{BR} (Note 3) (V)			@ I _T	V _C		I _{PP}
				Volts	nA	Min	Nom	Max	mA	V
MMBZ27VCL	KVP	22	50	25.65	27	28.35	1.0	38	1.0	+0.090

- Note:
- Device mounted on FR-5 PCB 1.0 x 0.75 x 0.062 inch pad layout as shown on Diodes Inc. suggested pad layout AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>. 200mW per element must not be exceeded.
 - Non-repetitive current pulse per Figure 2 and derate above T_A = 25°C per Figure 1.
 - Short duration test pulse used to minimize self-heating effect.
 - No purposefully added lead.




Fig. 1 Pulse Derating Curve




Fig. 2 Pulse Waveform




Fig. 3 Steady State Power Derating Curve




Fig. 4 Typical Capacitance vs. Bias Voltage
(Lower curve is Bidirectional mode,
Upper curve is Unidirectional)




Fig. 5 Typical Breakdown Voltage vs. Temperature (MMBZ27VCL)




Fig. 6 Typical Leakage Current vs. Temperature (MMBZ27VCL)




Fig. 7 Pulse Rating Curve,
 P_{pk} (W) vs. Pulse Width (ms)

Power is defined as $P_{pk} = V_c \times I_{pp}$




Fig. 8 Pulse Rating Curve,
 $P_{pk(NOM)}$ (W) vs. Pulse Width (ms)


Power is defined as $P_{pk(NOM)} = V_{BR(NOM)} \times I_{pp}$
where $V_{BR(NOM)}$ is the nominal breakdown voltage

Ordering Information (Note 5)

Device	Packaging	Shipping
MMBZ15VDL-7-F MMBZ27VCL-7-F	SOT-23	3000/Tape & Reel

Notes: 5. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



XXX = Product Type Marking Code, ex: KVP = MMBZ27VCL
YM = Date Code Marking
Y = Year ex: N = 2002
M = Month ex: 9 = September

Date Code Key

Year	2001	2002	2003	2004	2005	2006	2007	2008
Code	M	N	P	R	S	T	U	V

Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.