

3mm Round LED (T-1)

Features

- Popular T-1 diameter package
- Choice of various viewing angles
- Reliable and robust
- RoHS compliance

Descriptions

- The series is specially designed for applications requiring higher brightness.
- The LED lamps are available with different colors, intensities.



QRLNH4R3



Applications

- TV set
- Monitor
- Telephone
- Computer

Device Selection Guide

Part No.	Chip		Lens Color
	Material	Emitted Color	
TLN-H4R3-1254	GaP	Bright Red	Color Diffused

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Value	Unit
Reverse Voltage	VR	5	V
Continuous Forward Current	IF	15	mA
Power Dissipation	Pd	45	mW
Peak Forward Current (Duty 1/10@1KHZ)	IF	50	mA
Soldering Temperature (Note.1)	Tsol	260 ± 5	°C
Operating Temperature	Topr	-40 ~ +85	°C
Storage Temperature	Tstg	-40 ~ +100	°C







Note 1:

Soldering time ≤ 5 seconds


Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	0.63	1.60	-----	mcd	IF =10mA
Viewing Angle	2θ1/2	-----	40	-----	deg	
Peak wavelength	λp	-----	697	-----	nm	
Dominant wavelength	λd	-----	650	-----	nm	
Spectrum Radiation Bandwidth	Δλ	-----	90	-----	nm	
Forward Voltage	VF	1.5	2.0	2.4	V	VR=5V
Reverse Current	IR	-----	-----	10	μA	

Typical Electro-Optical Characteristics Curves (Ta=25°C)



Package Dimensions (In mm)



Note:


1. All dimensions are in millimeters, and tolerance is 0.25mm without special declared.
2. An epoxy meniscus may extend about 1.5mm down the lead.

Packing Quantity Specification

1. 1000 PCS/1 Bag, 5 Bags/1 Box
2. 10 Boxes/1 Carton

Ordering Information

TL N – H 4 R 3 – 1254– XX – BL



How to contact us

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO
C.P. 42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001
BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN'AN ROAD, SUITE 1502, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931