



## Sparkle Power Inc.

A Leading Power Supply manufacturer  
Web site: [www.sparklepower.com](http://www.sparklepower.com)



### FSP250-60SV

#### 250 Watts Flex ATX12V Switching Power Supply

#### Features

- Complied with ATX and ATX12V standard
- High efficiency and reliability
- Remote On/Off function
- Internal 12 VDC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 1950, CSA C22.2 Level 3, TUV 60950, NEMKO (CB Report)

#### Input Characteristics

**Input Range:** 90~132/180~264V AC, Manual-select

**Frequency:** 47~63 Hz

**Input Current:** 6A (RMS) @115V AC, 3A (RMS) @230V AC

**Inrush Current:** 35A Max for 115V AC, 70A Max for 230V AC Cold start

#### Specification

- **Temperature Range:** Operating 0° C ~ +25° C on full load; storage & shipping -20° C ~ +65° C
- **Humidity:** 90% on operating and 95% on storage
- **Dielectric Withstand:** Input to frame ground 1800V AC for 1 second
- **Efficiency:** 65% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 81x78x180mm/3.2"x3"x7.1" inches

#### Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	7.58/14 A	± 5%	± 1%	50mV P-P
+5V	1.5A	25/20.76 A	± 5%	± 1%	50mV P-P
+12V	0.5A	13A	± 5%	± 1%	120mV P-P
-5V	0.0A	0.3A	± 10%	± 2%	120mV P-P
-12V	0.0A	0.5A	± 10%	± 2%	120mV P-P
+5Vsb	0.0A	2.0 A	± 5%	± 1%	50mV P-P

\*+5V and +3.3V total output not exceed 150W

\*When +3.3V is load to 14A, the +5V maximum load is 20.76A

\*When +3.3V is load to 7.58A, the +5V maximum load is 25A

\*+3.3V, +5V, and +12V total output cannot exceed 232.5W

#### Sparkle Power Inc.

##### Main Office

1000 Rock Avenue  
San Jose, CA 95131  
TEL: 408-519-8888  
FAX: 408-519-9999  
E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

#### Sparkle Power Inc.

##### Los Angeles Office

17071 Green Drive  
City of Industry, CA 91745  
TEL: 626-839-7180  
FAX: 626-839-3395

#### Sparkle Power Inc.

##### Colorado Office

1316 Indian Paintbrush Lane  
Longmont, CO 80503  
TEL: 303-776-3281  
FAX: 303-776-7645