


PART NUMBER		REV.
SSB-DL10033GG		C
REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10222./	7-31-96
B	E.C.N. #10426./	4-6-98
C	E.C.N. #10BRDR. & REDRAWN.	10-29-98



NOTES:

1. TRANSPARENT ACRYLIC, FRONT SURFACE TO BE MATTE FINISH.
2. HIGH GREEN REFLECTIVE PAINT, BACK SURFACE.
3. PAINT EDGES WHITE, BOTH ENDS.
4. LEDS TO SNAP FIT INTO LDD. NO ADHESIVE TO BE USED.

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}\text{C}$ $I_f=20\text{ mA}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565 (GREEN)		nm	
FORWARD VOLTAGE		4.2	4.6	V_f	
REVERSE VOLTAGE	B			V_r	$V_r=200\mu\text{A}$
LUMINOUS INTENSITY		20		cd/m^2	$I_f=10\text{mA}$
EMITTED COLOR:	GREEN				
REFLECTOR FINISH:	GREEN				

LIMITS OF SAFE OPERATION AT 25°C PER LED

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	300	mA
STEADY CURRENT	20	mA
REVERSE VOLTAGE	B	V
POWER DISSIPATION	2.0	mW
DERATE FROM 25°C	-0.4	$\text{mW}/^{\circ}\text{C}$
OPERATING TEMP.	-20 TO +70	$^{\circ}\text{C}$
STORAGE TEMP.	-40 TO +80	$^{\circ}\text{C}$
SOLDERING TEMP.	+260	$^{\circ}\text{C}$
2.0mm FROM BODY	3 SEC. MAX	

* $t < 10\mu\text{s}$

*UNLESS OTHERWISE SPECIFIED TOLERANCE IS $\pm 0.25\text{mm}$ ($\pm 0.010''$)

REV.	PART NUMBER
C	SSB-DL10033GG

100mm x 33mm EDGE LIT LCD BACKLIGHT,
GREEN.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
INCORPORATED

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
PHONE: 1-847-359-2790
WEB: HTTP://WWW.LUMEX.COM

DRAWN BY:	CHECKED BY:	APPROVED BY:	DATE: 12-18-92
DU/BC			PAGE: 1 OF 1
			SCALE: N/A