



SURFACE MOUNT PLL-BASED PECL VCXO


SPECIFICATIONS	GV93-52*	GV93-53*	GV93-54*	GV93-62*	GV93-63*	GV93-64*
Available Frequency Ranges	120 to 135 MHz 144 to 168 MHz 174 to 205 MHz 232 to 270 MHz 288 to 336 MHz 348 to 410 MHz 464 to 540 MHz 576 to 672 MHz 700 to 800 MHz			144 to 168 MHz 174 to 205 MHz 288 to 336 MHz 348 to 410 MHz 576 to 672 MHz		
Frequency Stability	±50ppm	±100ppm	±20ppm	±50ppm	±100ppm	±20ppm
Operating Temp Range	0°C to +70°C			-40°C to +85°C		
Storage Temp Range	-55°C to +125°C					
Output	Waveform	PECL Squarewave , 100K Compatible				
	Load	Output must be terminated into 50 Ohms to 3Vdc.				
	Voltage Voh	4.0V Minimum , 4.5V Maximum				
	Vol	2.9V Minimum , 3.4V Maximum				
	Symmetry	45/55 Maximum measured at 50% level				
	Rise/Fall Time	750pS Maximum				
	Jitter	10pS rms Maximum , Full Bandwidth 3pS rms Maximum , 12KHz to 20MHz Bandwidth				
SSB Phase Noise	-100dBc/Hz typical @ 10KHz offset					
Frequency Control	Positive Transfer Characteristic					
Control Voltage	0.5 to 4.5Vdc					
Deviation @25°C	±75ppm Minimum , ±140ppm Maximum					
Center Frequency @25°C	Control Voltage 2.5Vdc ±0.5Vdc					
Linearity	< ±10%					
Input Impedance	> 50K ohms at < 10KHz					
Enable/Disable Option (Pin 1):	0.5Vdc Maximum 1.5Vdc Minimum Q (Pin 7) disables to low state, Option Q̄ (Pin 6) disables to high state. When Pin 1 is floating, output is in disabled state.					
Supply Voltage	+5Vdc ±5%					
Supply Current	100mA Maximum					
Package	Hermetically sealed, leadless ceramic package					
Options * - add suffix to model number	0	No Connection on Pin 1 and Pin 6				
	1	Complementary Output on Pin 6 , N/C on Pin 1				
	2	Enable/Disable on Pin 1 , N/C on Pin 6				
	3	Enable/Disable on Pin 1 , Complementary Output on Pin 6				



OUTPUT WAVEFORM



SUGGESTED PAD LAYOUT



TEST CIRCUIT

