

CTMFCR Series


FEATURES

- Advanced thin film technology.
- Excellent overall stability: Class 0.25
- Force fitted steel caps, tin plated on nickel barrier.
- Pure Sn termination on Ni barrier layer.
- Compatible with lead (Pb)-free and lead containing solering processes.
- Lead (Pb)-free and RoHS compliant

APPLICATIONS

- Military
- Automotive
- Telecommunication
- Medical equipment
- Avionics
- Space

PART NUMBERING



1. Product Type

Product Type	Metal Film Resistor
CTMFCR	

2. Dimensions (LxW)

EIA	Dimensions(LxW)
0204	3.45x1.35mm
0207	5.90x2.20mm

3. Resistance Tolerance


Codes	Resistance Tolerance
Q	±0.02%
A	±0.05%
B	±0.10%
C	±0.25%
D	±0.50%
F	±1.00%
J	±5.00%

4. Packaging

Code	Type
T	Tape & Reel

Tape & Reel QTY's

CTMFCR0204 = 3000pcs per reel
CTMFCR0207 = 2000pcs per reel



5. TCR

Codes	Type
B	±10 PPM/°C
N	±15 PPM/°C
C	±25 PPM/°C
D	±50 PPM/°C
E	±100 PPM/°C

6. Power Rating

Codes	Type
T	1W
U	1/2W
V	1/4W

7. Resistance


Codes	Type
R100	0.10Ω
0100	10.0Ω
2201	2200Ω
1002	10000Ω
4992	49900Ω
1003	100000Ω
1004	1000000Ω

05.05.08

CTMFCR Series

PHYSICAL DIMENSIONS

Codes	L	øD	K	L1 Min
0204	3.45±0.3	1.35±0.2	0.6±0.1	2.00
0207	5.90±0.3	2.20±0.2	1.0±0.1	3.40



STANDARD ELECTRICAL SPECIFICATIONS

Type	Power Rating at 70°C	Operating Temp. Range	Max. Operating Voltage	Resistance Tolerance (±)	Resistance Range	TCR (±PPM/°C)
CTMFCR0204	0.25W	-55°C to +155°C	200V	1%, 5%	0.1Ω-10MΩ	50, 200
				0.5%, 1%, 5%	1.0Ω-1MΩ	50
				0.1%, 0.25%, 0.5%, 1%	50Ω-200KΩ	10, 15, 25, 50
CTMFCR0207	0.50W	-55°C to +155°C	300V	1%, 5%	0.1Ω-10MΩ	50, 100
				0.5%, 1%, 5%	1.0Ω-1MΩ	50
				0.1%, 0.25%, 0.5%, 1%	50Ω-200KΩ	10, 15, 25, 50
				0.1%, 0.25%, 0.5%, 1%	50Ω-300KΩ	15, 25, 50

05.05.08

CTMFCR Series

ENVIRONMENTAL CHARACTERISTICS

Test Item		Requirements Permissible Change (ΔR)			Test Method
		0.25%	0.50%	0.50%	
Stability for product types	CTMFCR0204	50 Ω ~220K Ω	10 Ω ~<50 Ω	>220K Ω	
	CTMFCR0207	50 Ω ~1M Ω	10 Ω ~<50 Ω	>1M Ω	
Temperature Coefficient of Resistance		As Spec			MIL-STD-202F Method 304 +25/-55/+25/+125/+25 $^{\circ}$ C
Short Time Overload		$\Delta R \pm 0.1\%$ no visible damage			JIS-C-5202-5.5 RCWV*2.5 or Max Overloading Voltage 5 seconds
Thermal Shock		$\Delta R \pm 0.1\%$	$\Delta R \pm 0.25\%$	$\Delta R \pm 0.1\%$	MIL-STD-202F Method 107G -55 $^{\circ}$ C~150 $^{\circ}$ C, 100 cycles
Load Life		$\Delta R \pm 0.25\%$	$\Delta R \pm 0.25\%$	$\Delta R \pm 0.50\%$	MIL-STD-202F Method 108A RCWV, 70 $^{\circ}$ C, 1.5 hours ON, 0.5 hours OFF, total 1000~1048 hours
Humidity (Steady State)		$\Delta R \pm 0.25\%$	$\Delta R \pm 0.50\%$	$\Delta R \pm 0.50\%$	MIL-STD-202F Method 103B 40 $^{\circ}$ C, 90~95%RH, RCWV 1.5 hours ON, 0.5 hours OFF, total 1000~1048 hours
Resistance to Dry Heat		$\Delta R \pm 0.50\%$	$\Delta R \pm 1.00\%$	$\Delta R \pm 1.00\%$	JIS-C-5202-7.2 96 hours @ +155 $^{\circ}$ C without load
Low Temperature Operation		$\Delta R \pm 0.25\%$	$\Delta R \pm 0.50\%$	$\Delta R \pm 0.50\%$	JIS-C-5202-7.1 1 hour, -65 $^{\circ}$ C, followed by 45 minutes of RCWV
Solderability		95%min coverage			MIL-STD-202F Method 208H 245 $^{\circ}$ C \pm 5 $^{\circ}$ C, 2 \pm 0.5 (sec)
Resistance to Soldering Heat		$\Delta R \pm 0.10\%$	$\Delta R \pm 0.25\%$	$\Delta R \pm 0.10\%$	MIL-STD-202F Method 210E 260 \pm 5 $^{\circ}$ C, 10 \pm 1 seconds
*Storage Temperature: 25 \pm 3 $^{\circ}$ C; Humidity <80%RH					

05.05.08



Manufacturer of Passive and Discrete Semiconductor Components
800-684-5322 Inside US **949-453-1811** Outside US

Copyright © 2008 by CT Magnetics, DBA Central Technologies. All rights reserved.

CT Magnetics reserves the right to make improvements or change specifications without notice