



Data Sheet



Product Category: VCXO Surface Mount

Series Number	Package	Description	Last Modified
561	5 x 7 Ceramic 6 Pad	HCMOS / TTL	Jan. 01 2007

FEATURES


- 2.0mm low profile
- Wave form symmetry of 40/60%
- SMD Version 6 Pad
- 3.3V operation (optional)
- Tape and Reel
- RoHs / Lead Free compliant



OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

PARAMETERS	CONDITIONS	CHARACTERISTICS		UNITS
Output Logic	-	HCMOS / TTL Output		-
Input Voltage (VDD)	-	3.3 ±10%	5.0 ±10%	VDC
Frequency Range (f₀)	-	1.5440 ~ 52.0		MHz
Operating Temperature (T_{OPR})	-	0 ~ +70 (Std.) / -40 ~ 85 (Option)		°C
Storage Temperature (T_{STG})	-	-55 ~ +125		°C
Overall Frequency Stability	a + b + c + d	±20, ±25, ±50, ±100 max.		PPM
	(a) Frequency Tolerance	Inclusive of Overall Stability		-
	(b) Temperature Stability	Inclusive of Overall Stability (Operating Temperature)		-
	(c) Input Voltage Stability	Inclusive of Overall Stability (VDD ±5%)		-
	(d) Load Stability	Inclusive of Overall Stability (RL ±5%)		-
Input Current (I_{DD})	-	10 ~ 25 max.	15 ~ 35 max.	mA
Aging	@ 25°C	±3 max.		PPM/Y
Rise Time (T_R) / Fall Time (T_F)	-	10 max. (0.4V to 2.4V / TTL; Waveform / HCMOS)		nS
Pin 1 Control Voltage Range	-	1.65 ±1.35	2.5 ±2	V
Output Voltage High "1" VOH	TTL Load	2.4 min.		VDC
	HCMOS Load	2.7 min.	VDD-0.5 min.	
Output Voltage Low "0" VOL	TTL Load	0.4 max.		VDC
	HCMOS Load	0.5 max.		
Duty Cycle	-	50 ±10 (Std.) / 50 ±5 (Option)		%
Start-Up Time (T_S)	-	10 max.		ms
Jitter	(One Sigma)	±25 max.		ps
Linearity	-	±20 (Std.) / ±10 (Option)		%



PACKAGE DIMENSIONS (mm)

Suggested Solder Pad Layout

PIN CONNECTIONS	
#1	Control Voltage
#2	Tri-State Enable High or No Connection
#3	CASE GND
#4	OUTPUT
#5	Tri-State Enable High or No Connection
#6	VDD

PART NUMBER GUIDE

Series Number	Frequency	Voltage Supply Option	Frequency Tolerance & Stability (max.)	Operating Temp. (°C)	Duty Cycle	Pulling Range	Linearity	Tri-State Position
561	- 12.0 M	- 3	E	N	- T	P1	20	A
Oscilent VCXO	Enter your desired frequency e.g. 12.0M for 12.000MHz	5 = 5VDC 3 = 3.3VDC	D = ±100 PPM E = ±50 PPM F = ±25 PPM G = ±20 PPM H = ±10 PPM J = ±30 PPM	Blank* = 0~+70 N = -40~+85	Blank* = 50±10% T = 50±5%	P1 = ±50PPM P2 = ±100PPM P3 = ±150PPM (5V only) P4 = ±30PPM P5 = ±75PPM P6 = ±60PPM	20 = ±20% 10 = ±10% 05 = ±5%	A = Pin #2 B = Pin #5
<p>NOTE: - Deviations on all parameters available. Please consult Oscilent for details.</p> <p>DEFINITIONS: - Click on the characteristic names above for definitions of that particular characteristic.</p> <p>*STANDARDS: - "Blank" part number selections indicate standard variables for that particular characteristic.</p> <p>PACKAGING: - Standard tube packaging, add -TR for Tape/Reel. Click here for tape/reel specifications</p>								

Oscilent Corporation - CALL 949.252.0522

Series No.: 561

18195 East McDermott Street . Building D . Irvine . CA 92614 . USA
 Fax: 949.252.0599 . E-Mail: Sales@Oscilent.com