

Power Supply Cord with Special Connector and Plug, Straight

**Description**

Power Cord,
- Protection class II, Pin temperature 70 °C, Cable

References

[General Product Information](#)

Weblinks

[Approvals, RoHS, CHINA-RoHS, Mating Connectors, e-Store, Distributor-Stock-Check, Accessories](#)

Technical Data

Dielectric Strength	> 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black or grey

Config. Code

[Product Configurator](#)

5026 - R - Type - D - Length

The characters are placeholders for the correspondingly keys of selections from the key tables.
Typ steht für die Dose bzw. 2. Seite, Länge ist die Leitungslänge in mm.

5026 - R - Type - D - Length = cord type

cord type	Configuration key
special cord	Z

Cord definition is detailed in general product information XXX

5026 - R - Type - D - Length = Color

Color	Configuration key
jet black; RAL9005	A

standard color: black

5026 - R - Type - D - Length = Cord end 2

Cord end 2
zzzz

5026 - R - Type - D - Length = Cord length

Cord length
zzzz

Cord length in mm