



NOTE:  
2522A-08□□□-Q

1. Selective plating
- G1T-05u' Min gold in contact area/  
100u' Min. Tin in solder area.
  - G2T-Gold flash in contact area/  
100u' Min. Tin in solder area.
  - G3T-10u' Min gold in contact area/  
100u' Min. Tin in solder area.
  - G4T-15u' Min gold in contact area/  
100u' Min. Tin in solder area.
  - G5T-30u' Min gold in contact area/  
100u' Min. Tin in solder area.
  - G6T-50u' Min gold in contact area/  
100u' Min. Tin in solder area.

5	Top Shell	Stainless Steel	—	NI
4	Middle Shell	Stainless Steel	—	NI
3	Terminal	Phos.Bronze	—	GL0D/TIN
2	Shell	Stainless Steel	—	NI
1	Plastic	LCP	BLACK	UL90V-0
NO.	DESCRIPTION	MATERIAL	COLOR	REMARK

**SUYIN**  
CONNECTOR

CUSTOMER COPY TITLE: USB Series A Type Dual Port Dip Type

					Angle	±2°	DRAW	鄭家奇	01/07/04	PART NO.	
					30 ~	±0.50	DESIGN	鄭家奇	01/07/04	PART NO. (OLD)	2522A-08GXT-Q
					10 ~ 30	±0.30	CHECK	宋權哲	01/07/04	DRAWING NO.	D ING 2522A-08GXT-Q
					~ 10	±0.15	APPRO.	宋權哲	01/07/04	SCALE	4:1
ECN (DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED				UNIT	mm
										A4	⊕