www.molexkits.com



General Information	n			
Part Number:	76650-0123			
Manufacturer:	Molex / Waldom			
Title:	Picoflex Connector Kit			
Description:	SMT Vertical Header and IDT Receptacle			
Product Family:	Picoflex®			
Certificates:	RoHS Compliant, UL, CSA			
Country of Origin:	Kit assembled in U.S.A.			
Specifications				
Design Configuration:	Wire-to-Board			
Pitch:	1.27mm (.050")			
Connector Type:	Insulation Displacement Technology Receptacles and Vertical SMT Headers			
Mounting Orientation:	Vertical			
Circuit Sizes:	4, 6, 8, 10, 12, and 16			
Current Rating:	1.2 Amps			
Voltage:	250 Volts			
Flat Cable size:	28-26 AWG			
Product Highlights				
	Picoflex has a mated height of 6.40mm for vertical mating configurations, which is approximately 15% less that traditional .050" connector systems. A strong one- piece upper housing provides excellent cable retention and is ideal for small circuit size application. The high-reliability contact features a four-point interface with the cable and two points of contact between the header and receptacle. Picoflex also offers excellent polarization to both the PCB and between the female connector and header.			

Features and Benefits	Applications
 Mates with industry standard .050" cable Two points of contact between the header and receptacle Tested to meet the high vibration/shock 	 Car Radios Televisions Computer Peripherals Telecommunications

requirements of automotive and consumer

electronics industries



Bill of Materials for Part No. 76650-0123

Molex Part No.	Country of Origin	Description	Quantity in Kit
90814-0804	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 4 Circuits	2
90814-0806	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 6 Circuits	2
90814-0808	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 8 Circuits	2
90814-0810	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 10 Circuits	2
90814-0812	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 12 Circuits	2
90814-0816	Ireland	1.27mm (.050") Pitch Picoflex® PF-50 SMT Header, Vertical, Low Profile, with PCB Pegs, 16 Circuits	2
90327-0304	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 4 Circuits, White, Tin Plated	2
90327-0306	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 6 Circuits, White, Tin Plated	2
90327-0308	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 8 Circuits, White, Tin Plated	2
90327-0310	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 10 Circuits, White, Tin Plated	2
90327-0312	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 12 Circuits, White, Tin Plated	2
90327-0316	Ireland	1.27mm (.050") Pitch Picoflex® PF-50, Low Profile, IDT Receptacle, 16 Circuits, White, Tin Plated	2