


SAW Bandpass Filter 203405B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	203405B	
		Rev. Date	2004-04-26	
		Rev.	NI0029-CS02	1/5

SAW Bandpass Filter 203405B



3. Specifications

Fo = 80.495 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	80.445	80.495	80.545
Insertion Loss	dB	-	23.5	25.0
1dB Bandwidth	MHz	-	9.55	-
3dB Bandwidth	MHz	9.7	10.0	-
40dB Bandwidth	MHz	-	11.1	12.0
Amplitude Ripple (Fo +/- 4.4 MHz)	dB	-	1.4	1.9
Group Delay Variation (Fo +/- 4.4 MHz)	nsec	-	80	150
Absolute Delay	usec	-	2.96	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	203405B	
		Rev. Date	2004-04-26	
		Rev.	NI0029-CS02	2/5

SAW Bandpass Filter 203405B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$L1 = 100 \text{ nH}, \quad L2 = 47 \text{ nH}$

$C1 = C2 = 24 \text{ pF}$

5. Marking Configuration

ITF¹⁾ 04A001²⁾

203405B³⁾

1) Manufacturer name

2) Lot Number



3) Part Number

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	203405B	
		Rev. Date	2004-04-26	
		Rev.	NI0029-CS02	3/5

SAW Bandpass Filter 203405B



6. Typical Performance (at +25°C)



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.

203405B

Rev. Date





2004-04-26

Rev.

NI0029-CS02

4/5

SAW Bandpass Filter 203405B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

203405B

Rev. Date

2004-04-26

Rev.

NI0029-CS02

5/5