



Dimensions in (---) = 50pos.

No. of pos.	A -0.76	B -0.25	C	Part No:
9	31.19	16.46	25.00 $^{+0.12}_{-0.13}$	165X13129X
15	39.52	24.79	33.30 $^{+0.15}_{-0.1}$	165X13139X
25	53.42	38.50	47.04 ± 0.13	165X13149X
37	69.70	54.96	63.50 ± 0.13	165X13159X (165X13349X / 165X13159X-S)
50	67.31	52.55	61.10 $^{+0.14}_{-0.11}$	165X13169X

NOTES:

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- CONNECTOR IS PART MARKED: PART NO: CONEC ABC

Directive 2002/95/EC
„RoHS“
Compliant

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

				tolerance			
				2002	date	name	
				drawn	24.07.	Schmidt	
				appd.	24.07.	Mickenbecker	
				norm	DIN 41652		
				d-old	KAT11Y4A		
1 x b	Ä3162	29.10.2008	Sonne				
a	Origin						
rev.	description	date	name				

CONEC®

AutoCAD 2000
16K1A716
DIN-A
4
sh: 1/1