

rev 0.2

## Low Cost Frequency Multiplier

### Features

- Generates 4X clocks of the Input Clock frequency
- Input clock frequency range from 20 MHz to 78 MHz
- Provides up to 312 MHz Output Clock frequency
- External loop filter
- Low Cycle-to-cycle jitter
- 3.3 V Operating Voltage
- TTL or CMOS compatible outputs
- Ultra-low power CMOS design
- Available in Commercial and Industrial temperature ranges
- Available in 8-pin SOIC and TSSOP Packages

### Product Description

The P2384A is a versatile frequency multiplier that is designed specifically as cost effective alternative to the high precision frequency oscillator.


The P2384A can generate a 4X output clock of the input frequency that allows system cost savings by using an inexpensive crystal or resonator to achieve high frequency multiplication.

The P2384A provides up to 312 MHz output clock frequency through the use of the Phase-Lock-Loop (PLL) technique which delivers low jitter and high precision synthesized clocks.

### Applications


The P2384A is targeted towards the high frequency CAN OSC replacement market. Applications include xDSL, routers, networking, PC peripherals, and embedded systems.

### Block Diagram



rev 0.2

Pin Configuration



Pin Description

Pin#	Pin Name	Type	Description
1	XIN	I	Crystal connection or external reference frequency input
2	XOUT	O	Crystal connection. If using an external reference, this pin must be left unconnected.
3	PDB	I	Power-down control pin. Pull low to enable power-down mode. Connect directly to VDD in normal operation and if not used.
4	LF	I	External loop filter for the PLL. (See Loop Filter Selection Table for value.)
5	VSS	P	Ground connection. Connect to system ground.
6	CLKOUT	O	Clock output.
7	FS0	I	Digital logic input used to select Input frequency range. (See Input Frequency Selection.) This pin has an internal pull-up resistor.
8	VDD	P	Connect to +3.3 V.


Input Frequency Selection

FS0	Input (MHz)	Output Frequency Scaling (MHz)
0	20 to 38	80 to 152
1	39 to 78	156 to 312

February 2007

rev 0.2


Loop Filter Selection Table ( VDD 3.3 V )



Input (MHz)	FS0	C1(pF)	C2(pF)	R1 (ohms)
20	0	270	100,000	330
21 - 22	0	270	100,000	390
23 - 24	0	270	100,000	510
25 - 26	0	270	100,000	560
27 - 28	0	270	100,000	620
29 - 30	0	270	100,000	750
31 - 32	0	270	100,000	820
33 - 34	0	270	100,000	910
35 - 36	0	270	100,000	1,000
37 - 38	0	270	100,000	1,200
39 - 42	1	270	100,000	330
43 - 46	1	270	100,000	390
47 - 50	1	270	100,000	510
51 - 54	1	270	100,000	560
55 - 58	1	270	100,000	620
59 - 62	1	270	100,000	750
63 - 66	1	270	100,000	820
67 - 70	1	270	100,000	910
71 - 74	1	270	100,000	1,000
75 - 78	1	270	100,000	1,200

**Output Clock Selection Example**

The P2384A can generate 4X Clock from the Input reference frequency. P2384A's internal crystal oscillator circuits allow the use of an inexpensive crystal or resonator to replace expensive CAN oscillators that are used in networking, PC peripherals, xDSL, and consumer applications for high frequency generation. Its input frequency range is optimized for operations from 20 MHz to 78 MHz, and its output frequency can deliver up to 312 MHz.



PRELIMINARY

**Absolute Maximum Ratings**

Symbol	Parameter	Rating	Unit
$V_{DD}, V_{IN}$	Voltage on any pin with respect to Ground	-0.5 to +4.6	V
$T_{STG}$	Storage temperature	-65 to +125	°C
$T_A$	Operating temperature	-40 to +85	°C
$T_s$	Max. Soldering Temperature (10 sec)	260	°C
$T_J$	Junction Temperature	150	°C
$T_{DV}$	Static Discharge Voltage (As per JEDEC STD 22- A114-B)	2	KV

Note: These are stress ratings only and are not implied for functional use. Exposure to absolute maximum ratings for prolonged periods of time may affect device reliability.

**DC Electrical Characteristics**

Symbol	Parameter	Min	Typ	Max	Unit
$V_{IL}$	Input low voltage	VSS - 0.3	-	0.8	V
$V_{IH}$	Input high voltage	2.0	-	VDD + 0.3	V
$I_{IL}$	Input low current (Internal input pull-up resistor on FS0 and PDB)	-	180	-	µA
$I_{IH}$	Input high current (Internal input pull-up resistor on FS0 and PDB)	-	0	-	µA
$I_{XOL}$	XOUT output low current	-	10	-	mA
$I_{XOH}$	XOUT output high current	-	10	-	mA
$V_{OL}$	Output low voltage ( $V_{DD} = 3.3$ V, $I_{OL} = 20$ mA)	-	-	0.4	V
$V_{OH}$	Output high voltage ( $V_{DD} = 3.3$ V, $I_{OH} = 20$ mA)	2.5	-	-	V
$I_{DD}$	Static supply current*	-	3	-	mA
$I_{CC}$	Typical dynamic supply current (25 pF scope probe loading)	-	28	-	mA
$V_{DD}$	Operating voltage	3.0	3.3	3.6	V
$t_{ON}$	Power-up time	-	7	-	mS
$Z_{OUT}$	Clock output impedance	-	28	-	Ω

\* XIN and PBD are pulled low.

AC Electrical Characteristics


Symbol	Parameter	Min	Typ	Max	Unit
$f_{IN}$	Input frequency	20	–	78	MHz
$f_{OUT}$	Output frequency	80	–	312	MHz
$t_{LH}^*$	Output rise time (measured at 0.8 V to 2.0 V)	–	1	–	nS
$t_{HL}^*$	Output fall time (measured at 2.0 V to 0.8 V)	–	1	–	nS
$t_{JC}$	Jitter (cycle to cycle)	–	±200	–	pS
$t_D$	Output duty cycle	45	50	55	%

\*  $t_{LH}$  and  $t_{HL}$  are measured into a capacitive load of 15 pF

PRELIMINARY


Package Information

8-lead (150-mil) SOIC Package



Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A1	0.004	0.010	0.10	0.25
A	0.053	0.069	1.35	1.75
A2	0.049	0.059	1.25	1.50
B	0.012	0.020	0.31	0.51
C	0.007	0.010	0.18	0.25
D	0.193 BSC		4.90 BSC	
E	0.154 BSC		3.91 BSC	
e	0.050 BSC		1.27 BSC	
H	0.236 BSC		6.00 BSC	
L	0.016	0.050	0.41	1.27
theta	0°	8°	0°	8°

8-lead Thin Shrunk Small Outline Package (4.40-MM Body)



Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A		0.043		1.10
A1	0.002	0.006	0.05	0.15
A2	0.033	0.037	0.85	0.95
B	0.008	0.012	0.19	0.30
c	0.004	0.008	0.09	0.20
D	0.114	0.122	2.90	3.10
E	0.169	0.177	4.30	4.50
e	0.026 BSC		0.65 BSC	
H	0.252 BSC		6.40 BSC	
L	0.020	0.028	0.50	0.70
$\theta$	0°	8°	0°	8°




rev 0.2

Ordering Codes

Part Number	Marking	Package Type	Qty per reel	Temperature
P2384A-08ST	P2384AG	8-pin SOIC, Tube, GREEN		Commercial
P2384A-08SR	P2384AG	8-pin SOIC, Tape & reel, GREEN	2500	Commercial
P2384A-08TT	P2384AG	8-pin TSSOP, Tube, GREEN		Commercial
P2384A-08TR	P2384AG	8-pin TSSOP, Tape & reel, GREEN	2500	Commercial
I2384A-08ST	I2384AG	8-pin SOIC, Tube, GREEN		Industrial
I2384A-08SR	I2384AG	8-pin SOIC, Tape & reel, GREEN	2500	Industrial
I2384A-08TT	I2384AG	8-pin TSSOP, Tube, GREEN		Industrial
I2384A-08TR	I2384AG	8-pin TSSOP, Tape & reel, GREEN	2500	Industrial
P2384AF-08ST	P2384AF	8-pin SOIC, Tube, Pb Free		Commercial
P2384AF-08SR	P2384AF	8-pin SOIC, Tape & reel, Pb Free	2500	Commercial
P2384AF-08TT	P2384AF	8-pin TSSOP, Tube, Pb Free		Commercial
P2384AF-08TR	P2384AF	8-pin TSSOP, Tape & reel, Pb Free	2500	Commercial
I2384AF-08ST	I2384AF	8-pin SOIC, Tube, Pb Free		Industrial
I2384AF-08SR	I2384AF	8-pin SOIC, Tape & reel, Pb Free	2500	Industrial
I2384AF-08TT	I2384AF	8-pin TSSOP, Tube, Pb Free		Industrial
I2384AF-08TR	I2384AF	8-pin TSSOP, Tape & reel, Pb Free	2500	Industrial

Device Ordering Information



Licensed under US patent Nos 5,488,627 and 5,631,920.

*Giving you the edge*

PulseCore Semiconductor Corporation  
1715 S. Bascom Ave Suite 200  
Campbell, CA 95008  
Tel: 408-879-9077  
Fax: 408-879-9018  
[www.pulsecoresemi.com](http://www.pulsecoresemi.com)

Copyright © PulseCore Semiconductor  
All Rights Reserved  
Part Number: P2384A  
Document Version: v0.2

Note: This product utilizes US Patent # 6,646,463 Impedance Emulator Patent issued to PulseCore Semiconductor, dated 11-11-2003

© Copyright 2007 PulseCore Semiconductor Corporation. All rights reserved. Our logo and name are trademarks or registered trademarks of PulseCore Semiconductor. All other brand and product names may be the trademarks of their respective companies. PulseCore reserves the right to make changes to this document and its products at any time without notice. PulseCore assumes no responsibility for any errors that may appear in this document. The data contained herein represents PulseCore's best data and/or estimates at the time of issuance. PulseCore reserves the right to change or correct this data at any time, without notice. If the product described herein is under development, significant changes to these specifications are possible. The information in this product data sheet is intended to be general descriptive information for potential customers and users, and is not intended to operate as, or provide, any guarantee or warranty to any user or customer. PulseCore does not assume any responsibility or liability arising out of the application or use of any product described herein, and disclaims any express or implied warranties related to the sale and/or use of PulseCore products including liability or warranties related to fitness for a particular purpose, merchantability, or infringement of any intellectual property rights, except as express agreed to in PulseCore's Terms and Conditions of Sale (which are available from PulseCore). All sales of PulseCore products are made exclusively according to PulseCore's Terms and Conditions of Sale. The purchase of products from PulseCore does not convey a license under any patent rights, copyrights; mask works rights, trademarks, or any other intellectual property rights of PulseCore or third parties. PulseCore does not authorize its products for use as critical components in life-supporting systems where a malfunction or failure may reasonably be expected to result in significant injury to the user, and the inclusion of PulseCore products in such life-supporting systems implies that the manufacturer assumes all risk of such use and agrees to indemnify PulseCore against all claims arising from such use.