

RECTIFIER DEVICE - Phase Control Thyristors - Stud Types

Old Part Number	PDF Data Sheet Available	New Part Number	V _{DRM} V _{RRM} Range		I _{T(AV)} at T _{SINK} 25°C		I _{T(RMS)} at T _{SINK} 25°C	I _T at T _{SINK} 25°C	I _{TSM(1)} 10ms V _R £60% V _{RRM}	I _{TSM(2)} 10ms V _R £10V V _{RRM}	I ² t ₍₂₎	di/dt Non-Rep /Rep	I _{GT} /V _{GT} at 25°C	I _{DRM} I _{RRM} at 125°C	I _H at 25°C	Rth j-c		Rth c-s	V _o r at T _j 125°C	V _{TM} at I _{TM} at T _j 125°C	Wt (typ.)	Mounting Torque	Outline No. (Note 4)
			Note 5 (V)	(A) (°C)	(A)	(A)	Note 1 (A)	Note 1 (A)	Note 1 (A2s)	Note 4 (A/ms)	(mA)/(V)	(mA)	(mA)	dc 180°sine (K/W)	120° Rect (K/W)	(K/W)	Note 2 (V) (mW)	(V) / (A)	(g)	(kgf·m ⁻¹)			
N086PH12-16	N	N0131SP120-160	1200-1600	131	(55)	175	175	1700	1950	19 x 10 ³	1000/500	150/3	20	600	0.23	0.28	0.08	1.57	2.29	2.29/315	130	1.45 - 1.15	101A235 or 101A231
N105PH12-16	N	N0180SP120-160	1200-1600	180	(55)	175	175	2450	2695	36.3 x 10 ³	1000/500	150/3	20	600	0.23	0.28	0.08	0.90	1.79	1.46/315	130	1.45 - 1.15	
N170PH12-16	N	N0290SP120-160	1200-1600	290	(55)	355	355	4200	4620	107 x 10 ³	1000/500	150/3	20	600	0.12	0.14	0.04	1.08	1.30	1.98/690	280	2.77 - 2.5	101A225
N195PH12-16	N	N0335SP120-160	1200-1600	335	(55)	355	355	4650	5120	131 x 10 ³	1000/500	150/3	20	600	0.12	0.14	0.04	0.92	0.99	1.60/690	280	2.77 - 2.5	
N275PH02-08	N	N0416SP020-080	200-800	416	(55)	355	355	6000	6600	218 x 10 ³	1000/500	150/3	20	400	0.12	0.14	0.04	0.85	0.535	1.22/690	280	2.77 - 2.5	

The information contained herein is confidential and is protected by Copyright. The information may not be used or disclosed except with the written permission of and in the manner permitted by the proprietors Westcode Semiconductors Limited. In the interest of product improvement, Westcode reserves the right to change specifications at any time without prior notice.

- Note 1 $I_{TSM}(8.3ms) = I_{TSM}(10ms) \times 1.066$ $I^2t(8.3ms) = I^2t(10ms) \times 0.943$
- Note 2 V_o Threshold Voltage
r Slope resistance) for conduction loss and heatsink calculations. (T_j = 125°C)
- Note 3 A blocking voltage derating factor of 0.13% per degree centigrade is applicable for T_j below 25°C
- Note 4 di/dt ratings refer to the sum of snubber discharge and load currents.
- Note 5 Outline 101A153 - leaded types available, code changes from RH to PH. Lead length 146mm (base of hexagon to centre of lug hole).