

2SK1692

HIGH SPEED, HIGH CURRENT SWITCHING APPLICATIONS.
CHOPPER REGULATOR APPLICATIONS.

- Low Drain-Source ON Resistance : $R_{DS(ON)} = 1.7\Omega$ (Typ.)
- High Forward Transfer Admittance : $|Y_{fs}| = 4.0S$ (Typ.)
- Low Leakage Current : $I_{DSS} = 300\mu A$ (Max.) @ $V_{DS} = 720V$
- Enhancement-Mode : $V_{th} = 1.5\sim 3.5V$ @ $V_{DS} = 10V, I_D = 1mA$

MAXIMUM RATINGS (Ta = 25°C)


CHARACTERISTIC		SYMBOL	RATING	UNIT
Drain-Source Voltage		V_{DSS}	900	V
Drain-Gate Voltage ($R_{GS} = 20k\Omega$)		V_{DGR}	900	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	DC	I_D	7	A
	Pulse	I_{DP}	21	
Drain Power Dissipation ($T_c = 25^\circ C$)		P_D	150	W
Channel Temperature		T_{ch}	150	°C
Storage Temperature Range		T_{stg}	$-55\sim 150$	°C

THERMAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MAX.	UNIT
Thermal Resistance, Channel to Case	$R_{th(ch-c)}$	0.833	°C / W
Thermal Resistance, Channel to Ambient	$R_{th(ch-a)}$	50	°C / W


THIS TRANSISTOR IS AN ELECTROSTATIC SENSITIVE DEVICE.
PLEASE HANDLE WITH CAUTION.

INDUSTRIAL APPLICATIONS
Unit in mm



Weight : 4.6g

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I_{GSS}	$V_{GS} = \pm 25V, V_{DS} = 0V$	—	—	± 100	nA
Drain Cut-off Current		I_{DSS}	$V_{DS} = 720V, V_{GS} = 0V$	—	—	300	μA
Drain-Source Breakdown Voltage		$V_{(BR) DSS}$	$I_D = 10mA, V_{GS} = 0V$	900	—	—	V
Gate Threshold Voltage		V_{th}	$V_{DS} = 10V, I_D = 1mA$	1.5	—	3.5	V
Drain-Source ON Resistance		$R_{DS(ON)}$	$I_D = 3.5A, V_{GS} = 10V$	—	1.7	2.0	Ω
Forward Transfer Admittance		$ Y_{fs} $	$V_{DS} = 10V, I_D = 3.5A$	2.0	4.0	—	S
Input Capacitance		C_{iss}	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$	—	900	—	pF
Reverse Transfer Capacitance		C_{rss}		—	80	—	
Output Capacitance		C_{oss}		—	150	—	
Switching Time	Rise Time	t_r	 $V_{IN} : t_r, t_f < 5ns, V_{DD} \doteq 400V$ Duty $\leq 1\%, t_W = 10\mu s$	—	70	—	ns
	Turn-on Time	t_{on}		—	100	—	
	Fall Time	t_f		—	100	—	
	Turn-off Time	t_{off}		—	360	—	
Total Gate Charge (Gate-Source Plus Gate-Drain)		Q_g	$V_{DD} \doteq 400V, V_{GS} = 10V, I_D = 7A$	—	70	—	nC
Gate-Source Charge		Q_{gs}		—	40	—	
Gate-Drain ("Miller") Charge		Q_{gd}		—	30	—	

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Continuous Drain Reverse Current	I_{DR}	—	—	—	7	A
Pulse Drain Reverse Current	I_{DRP}	—	—	—	21	A
Diode Forward Voltage	V_{DSF}	$I_{DR} = 7A, V_{GS} = 0V$	—	—	−2.0	V

961001EAA2'

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

