

SAFETY ORGANIZATION(S).

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY, THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET.

UL 1283
CSA 22.2, NO.0.0.4.8
VDE 565-3
SEV 1055/TP1977/5.1.1

OPERATING SPECIFICATIONS.

LINE VOLTAGE/CURRENT:
20 AMP., 120/250 VAC
16 AMP./40°C, 250 VAC
50-60Hz
30°C
.25mA at 120V 50 Hz
.40 mA at 250V 50 Hz
LINE TO GROUND
MAX. LEAKAGE CURRENT, EACH
MAX. CASE RISE & RATED CURRENT,
LINE FREQUENCY,
IN AN AMBIENT, I_o , HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_o , IS AS FOLLOWS,
 $I_o = I_r \sqrt{\frac{95-I_o}{45}}$
-40°C TO +85°C
21 DAYS @ 40°C 95% RH
6 TIMES RATED CURRENT FOR 8 SECONDS

RELIABILITY SPECIFICATIONS.

STORAGE TEMPERATURE,
HUMIDITY,
CURRENT OVERLOAD TEST,
TEST SPECIFICATIONS:
INDUCTANCE,
CAPACITANCE, (MEASURED @ 1 KHz, 0.25 VAC MAX., 25°C ±1°C)
LINE TO GROUND,
LINE TO LINE,
DISCHARGE RESISTOR
LINE/GROUND AND LINE/LINE
INSULATION RESISTANCE

RECOMMENDED RECEIVING INSPECTION HIPO.

2250 VDC FOR 1 MINUTE
1450 VDC FOR 1 MINUTE
2250 VDC FOR 1 MINUTE
1450 VDC FOR 1 MINUTE
2250 VDC FOR 1 MINUTE
1450 VDC FOR 1 MINUTE
2250 VDC FOR 1 MINUTE
1450 VDC FOR 1 MINUTE

FILTER APPROVAL.

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.

50a - 50a (MINIMUM) INSERTION LOSS											
FREQUENCY MHz	.15	.3	.5	1	2	5	10	20	30		
COMMON	2	21	36	56	65	65	60	54	50		
DIFF.	2	3	2	55	65	65	65	55	50		

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.

TOLERANCE EXCEPT AS NOTED
DECIMAL: .XXX .XX .X ANGLES
ENGLISH: ±.025
METRIC: ±
MATERIAL:
AS SUPPLIED
FINISH:
AS SUPPLIED

corcom
LIBERTYVILLE, IL 60048
POWER LINE FILTER

SCALE NTS 9-12-89
DATE 9-12-89
REV. NO. 20ER1.04
ORIGINATOR CW
BY TDL

