

Linear Systems replaces discontinued Siliconix SST4392

The SST4392 features many of the superior characteristics of JFETs which make it a good choice for demanding analog switching applications and for specialized amplifier circuits.

SST4392 Benefits:

- Low Error Voltage
- High-Speed Analog Circuit Performance
- Negligible "Off-Error," Excellent Accuracy
- Good Frequency Response, Low Glitches
- Eliminates Additional Buffering

SST4392 Applications:

- Analog Switches
- Choppers, Sample-and-Hold
- Normally "On" Switches, Current Limiters

FEATURES

DIRECT REPLACEMENT FOR SILICONIX SST4392	
LOW ON RESISTANCE	$r_{DS(on)} \leq 60\Omega$
LOW GATE OPERATING CURRENT	$I_{D(off)} = 5\mu A$
FAST SWITCHING	$t_{(ON)} \leq 15ns$
ABSOLUTE MAXIMUM RATINGS¹ @ 25°C (unless otherwise noted)	
Maximum Temperatures	
Storage Temperature	-65°C to +200°C
Operating Junction Temperature	-55°C to +200°C
Maximum Power Dissipation	
Continuous Power Dissipation	350mW
MAXIMUM CURRENT	
Gate Current (Note 1)	$I_G = 50mA$
MAXIMUM VOLTAGES	
Gate to Drain Voltage / Gate to Source Voltage	-35V

SST4392 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
BV_{GSS}	Gate to Source Breakdown Voltage	-35	--	--	V	$I_G = -1\mu A, V_{DS} = 0V$
$V_{GS(off)}$	Gate to Source Cutoff Voltage	-2	--	-5		$V_{DS} = 15V, I_D = 10nA$
$V_{GS(F)}$	Gate to Source Forward Voltage	--	0.7	1		$I_G = 1mA, V_{DS} = 0V$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.25	--	mA	$V_{GS} = 0V, I_D = 3mA$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.3	0.4		$V_{GS} = 0V, I_D = 6mA$
$V_{DS(on)}$	Drain to Source On Voltage	--	0.35	--		$V_{GS} = 0V, I_D = 12mA$
I_{DSS}	Drain to Source Saturation Current ²	25	--	--	pA	$V_{DS} = 20V, V_{GS} = 0V$
I_{GSS}	Gate Reverse Current	--	-5	-100		$V_{GS} = -20V, V_{DS} = 0V$
I_G	Gate Operating Current	--	-5	--		$V_{DG} = 15V, I_D = 10mA$
$I_{D(off)}$	Drain Cutoff Current	--	5	100	Ω	$V_{DS} = 10V, V_{GS} = -10V$
$r_{DS(on)}$	Drain to Source On Resistance	--	--	60		$V_{GS} = 0V, I_D = 1mA$

SST4392 DYNAMIC ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	TYP	MIN	MAX	UNITS	CONDITIONS
g_{fs}	Forward Transconductance	6	--	--	mS	$V_{DS} = 20V, I_D = 1mA, f = 1kHz$
g_{os}	Output Conductance	25	--	--	μS	$V_{DS} = 20V, I_D = 1mA, f = 1kHz$
$r_{ds(on)}$	Drain to Source On Resistance	--	--	60	Ω	$V_{GS} = 0V, I_D = 0A, f = 1kHz$
C_{iss}	Input Capacitance	13	--	--	pF	$V_{DS} = 20V, V_{GS} = 0V, f = 1MHz$
C_{rss}	Reverse Transfer Capacitance	3.6	--	--		$V_{DS} = 0V, V_{GS} = -5V, f = 1MHz$
C_{rss}		3.5	--	--		$V_{DS} = 0V, V_{GS} = -7V, f = 1MHz$
C_{rss}		3.1	--	--		$V_{DS} = 0V, V_{GS} = -12V, f = 1MHz$
e_n	Equivalent Input Noise Voltage	3	--	--	nV/√Hz	$V_{DS} = 10V, I_D = 10mA, f = 1kHz$

SST4392 SWITCHING ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)


SYMBOL	CHARACTERISTIC	TYP	MIN	MAX	UNITS	CONDITIONS
$t_{d(on)}$	Turn On Time	2	--	--	ns	$V_{DD} = 10V, V_{GS(H)} = 0V$
t_r		2	--	--		
$t_{d(off)}$	Turn Off Time	6	--	--		
t_f		13	--	--		

Notes: 1. Absolute ratings are limiting values above which serviceability may be impaired
2. Pulse test: PW ≤ 300μs, Duty Cycle ≤ 3%

SST4392 SWITCHING CIRCUIT PARAMETERS

$V_{GS(L)}$	-7V
R_L	1600Ω
$I_{D(on)}$	6mA

SOT-23 (Top View)



Available Packages:


SST4392 in SOT-23
SST4392 in bare die.

Micross Components Europe



Tel: +44 1603 788967
Email: chipcomponents@micross.com
Web: <http://www.micross.com/distribution>

SWITCHING CIRCUIT



Contact Micross for full package and die dimensions