

ASA Series

10 Watts

Total Power: 10 Watts
Input Voltage: 24V or 48V
of Outputs: Single



Special Features

- Encapsulated
- 2:1 input range
- 1.25" X 0.8" DIP package
- 1500Vdc I/O isolation
- Single output

Electrical Specifications

Input

Input range	18 to 36 VDC; 36 to 75 VDC
Efficiency ²	83%@12Vo

Output

Voltage tolerance	±2.0%
Line regulation	±0.8%
Load regulation	±1.2%
Noise/ripple	100mV for 2.5Vo, 3.3Vo and 5.0Vo 120mV for 12Vo
Short circuit protection	Auto-restart
Switching frequency	350KHz
Temperature coefficient	±0.02 /°C

Isolation

I/O isolation	1500 VDC min.
Insulation resistance	10Mohm
Insulation capacitance	1000pF

Environmental Specifications

Operating ambient temperature range	-40°C to +60°C (no derating)
Storage temperature	-55°C to +105°C
Humidity	5% to 95% (non-condensing)
MTBF	1 Mhrs demonstrated MTBF
RoHS Compliant	

Safety

CE Mark



Ordering Information

Input Voltage	Output 1 Voltage	Output 2 Voltage	Maximum Power	Model Number
18 - 36 V	2.5 V @ 3 A		7.5 W	ASA03G24-L
18 - 36 V	3.3 V @ 3 A		10 W	ASA03F24-L
18 - 36 V	5 V @ 2 A		10 W	ASA02A24-L
18 - 36 V	12 V @ 0.835 A		10 W	ASA00B24-L
36 - 75 V	2.5 V @ 3 A		7.5 W	ASA03G48-L
36 - 75 V	3.3 V @ 3 A		10 W	ASA03F48-L
36 - 75 V	5 V @ 2 A		10 W	ASA02A48-L
36 - 75 V	12 V @ 0.835 A		10 W	ASA00B48-L

Please contact Astec for information on other output voltages, power ranges and configurations.
Available in RoHS 6 version only.

Americas

5810 Van Allen Way
Carlsbad, CA 92008
USA
Telephone: +1 (760) 930 4600
Facsimile: +1 (760) 930 0698

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
Telephone: +44 (0) 1384 842 211
Facsimile: +44 (0) 1384 843 355

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
Telephone: +852 2176 3333
Facsimile: +852 2176 3888

For global contact, visit:

www.powerconversion.com

techsupport.embeddedpower@emerson.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

Emerson Network Power.


The global leader in enabling business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

EmersonNetworkPower.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
©2008 Emerson Electric Co.

Mechanical Drawing



Notes:

- All specifications subject to change without notice. Mechanical drawings are for reference only.
- Warranty: 1 yr
- Label and logo appearance may vary from what is shown on mechanical drawings.