7 Pin SIL 4 Tap TTL Compatible Active Delay Lines

TAP DELAYS ±5% or ±2 nS †	TOTAL DELAYS ±5% or ±2 nS†	Part Number	TAP DELAYS ±5% or ±2 nS†	TOTAL DELAYS ±5% or ±2 nS†	Part Number
1.0 ± 0.5	*3 ± 0.5	EPA1190-4	15	60	EPA1190-60
2.0 ± 1	*8 ± 1.0	EPA1190-6	20	80	EPA1190-80
3.0 ± 1	*9	EPA1190-9	25	100	EPA1190-100
4.0 ± 1.5	*12	EPA1190-12	30	120	EPA1190-120
5.0	*15	EPA1190-15	35	140	EPA1190-140
6.0	*18	EPA1190-18	40	160	EPA1190-160
7.0	28	EPA1190-28	50	200	EPA1190-200
8.0	32	EPA1190-32	60	240	EPA1190-240
9.0	36	EPA1190-36	70	280	EPA1190-280
10.0	40	EPA1190-40	80	320	EPA1190-320
12.0	48	EPA1190-48	90	360	EPA1190-360
			100	400	EPA1190-400

†Whichever is greater. Delay times referenced from input to leading edges at 25°C, 5.0V, with no load.
**Delay times referenced from 1st tap*
1st tap is the inherent delay: approx. 7 nS

DC Electrical Characteristics

	Parameter	Test Conditions	Min	Max	Unit
V_{OH}	High-Level Output Voltage	V_{CC} = min. V_{IL} = max. I_{OH} = max	2.7		V
V_{OL}	Low-Level Output Voltage	V_{CC} = min. V_{IH} = min. I_{OL} = max		0.5	V
V_{IK}	Input Clamp Voltage	V_{CC} = min. I_I = II_K		-1.2V	V
I_{IH}	High-Level Input Current	V_{CC} = max. V_{IN} = 2.7V		50	µA
		V_{CC} = max. V_{IN} = 5.25V		1.0	mA
I_{IL}	Low-Level Input Current	V_{CC} = max. V_{IN} = 0.5V		-2	mA
I_{OS}	Short Circuit Output Current	V_{CC} = max. V_{OUT} = 0. (One output at a time)	-40	-100	mA
I_{CCH}	High-Level Supply Current	V_{CC} = max. V_{IN} = OPEN		115	mA
I_{CCL}	Low-Level Supply Current	V_{CC} = max. V_{IN} = 0		115	mA
T_{RO}	Output Rise Time	Td ≤ 500 nS (0.75 to 2.4 Volts)		4	nS
N_H	Fanout High-Level Output	V_{CC} = max. V_{OH} = 2.7V		20 TTL LOAD	
N_L	Fanout Low-Level Output	V_{CC} = max. V_{OL} = 0.5V		10 TTL LOAD	

Schematic



Recommended Operating Conditions

		Min	Max	Unit
V_{CC}	Supply Voltage	4.75	5.25	V
V_{IH}	High-Level Input Voltage	2.0		V
V_{IL}	Low-Level Input Voltage		0.8	V
I_{IK}	Input Clamp Current		-18	mA
I_{OH}	High-Level Output Current		-1.0	mA
I_{OL}	Low-Level Output Current		20	mA
P_W*	Pulse Width of Total Delay	40		%
d*	Duty Cycle		40	%
T_A	Operating Free-Air Temperature	0	+70	°C

**These two values are inter-dependent.*

Input Pulse Test Conditions @ 25° C

			Unit
E_{IN}	Pulse Input Voltage	3.2	Volts
P_W	Pulse Width % of Total Delay	110	%
T_{RI}	Pulse Rise Time (0.75 - 2.4 Volts)	2.0	nS
P_{RR}	Pulse Repetition Rate @ Td ≤ 200 nS	1.0	MHz
	Pulse Repetition Rate @ Td > 200 nS	100	KHz
V_{CC}	Supply Voltage	5.0	Volts

Package Dimensions



Unless Otherwise Noted Dimensions in Inches
Tolerances:
Fractional = ± 1/32
.XX = ± .030 .XXX = ± .010

PCA ELECTRONICS INC.
16799 SCHOENBORN ST.
NORTH HILLS, CA 91343
TEL: (818) 892-0761
FAX: (818) 894-5791