

RESIN DIPPED TANTALUM ELECTROLYTIC CAPACITORS

SH SERIES

SH series is a high reliable resin dipped solid tantalum capacitor. This features long life (85°C, 2,000 hours), low leakage current and non-flammable epoxy resin use

Specifications

Operating temperature range -55°C to $+85^{\circ}\text{C}$

Rated working voltage range. 3.15 to 50 WV DC

Rated capacitance range: 0.1 to 470 μF

Capacitance tolerance (at 120 Hz/20°C)
 $\pm 20\%$ ($\pm 10\%$ is available)

■ DC leakage current

$I = 0.008 \text{ CV or } 0.05 \mu\text{A}$

Whichever is the greater

where, I max leakage current (μA)

C rated capacitance (μF)

V rated voltage (V)

The DC leakage current shall be measured after 2 minutes application of the rated dc working voltage through a 1,000 ohm resistor

Tan. δ (at 120 Hz/20°C)

0.04 max for 0.1 - 1 μF

0.06 max for 1.5 - 68 μF

0.08 max for 100 - 470 μF

0.10 max for 3V working products

refer to standard products table

■ Surge voltage

Working voltage	Surge voltage
3.15 V, DC	4 V, DC
6.3	8
10	13
16	20
25	32
35	44
50	63

The capacitor shall be applied with a surge voltage in series with a 1,000 ohm resistor at a cycle of 0.5 minutes "ON" and 4.5 minutes "OFF" repeating 1,000 times at $+85^{\circ}\text{C}$

After the test, the capacitor shall meet the following limits

Capacitance change	Within $\pm 5\%$ of the initial measured value
Tan δ	Less than the initial specified value
Leakage current	Less than the initial specified value

■ Low and high temperature stability

	-55°C	$+85^{\circ}\text{C}$
Capacitance change	$\pm 12\%$ max	$\pm 12\%$ max
Leakage current	—	0.1 CV or 5 μA max whichever is the greater

■ Humidity Life test

After testing for 500 hours at 40°C , 90~95% RH with no voltage applied, the capacitor shall meet the following limits

Capacitance change	Within $\pm 15\%$ of the initial measured value
Tan δ	Less than 150% of the initial specified value
Leakage current	Less than 150% of the initial specified value

■ Load Life test

After testing for 2,000 hours at 85°C with working voltage applied through a 1,000 ohm resistor, the capacitor shall meet the following limits

Capacitance change	Within $\pm 10\%$ of the initial measured value
Tan δ	Less than the initial specified value
Leakage current	Less than 125% of the initial specified value

■ Shelf life test

After testing 2,000 hours at 85°C with no voltage applied, the capacitor shall meet the limits of Load life test



DUBLIN SALES OFFICE
 LAUNTON ROAD
 BICESTER
 OXON
 (08692) 42035
 TWX 337504

DISTRIBUTORS
 FOR THE
 SH
 TANTALUM
 CAPACITORS

BARLEC
 Tel (0403) 51881
 Telex 877222

BOSLEDGE
 Tel 061 834 7339
 Telex 667864


RESIN DIPPED TANTALUM ELECTROLYTIC CAPACITORS

SH SERIES

Standard products table

W V (V DC) Cap (μF)	3 15	6.3	10	16	25	35	50
0.1				A		A	C
0.15				A		A	C
0.22				A		A	C
0.33				A		A	C
0.47				A		B	C
0.68				A		B	E
1.0				A		C	F
1.5				B	C	D	G
2.2				C	D	E	H
3.3			C	D	E	F	I
4.7		C	D	E	F	G	J
6.8	C	D	E	F	G	I	L
10	D	E	F	G	I	J	
15	E	F	G	H	J	K	
22	F	G	H	I	K	L	
33	G	H	I	J	L	M	
47	H	I	J	K	M	N	
68	I	J	K	L	N		
100	J	K	L	M			
150	K	L	M	N			
220	L	M	N				
330	M	N					
470	N						

SH type



Size code	D max	L max	F
A	3.5	6.0	5.0
B	4.0	6.5	5.0
C	4.0	7.0	5.0
D	4.5	7.0	5.0
E	4.5	7.5	5.0
F	4.5	8.0	5.0
G	5.0	8.0	5.0
H	5.0	8.5	5.0
I	5.5	9.0	5.0
J	6.0	10.0	5.0
K	7.5	11.0	5.0
L	7.5	12.0	5.0
M	9.0	14.0	5.0
N	10.0	15.0	5.0

Marking

"A" ~ "C" size products

W V code/place of decimal point
Ex V1 = 35V 0.1μF
V47 = 35V 0.47μF
2C2 = 16V 2.2μF

Capacitance

"D" ~ "N" size products

W V

W V code for marking on A - C size products

Code	W V
F	3 15
J	6.3
A	10
C	16
E	25
V	35
H	50

DTV
Tel 01 670 6166
Telex 262415

FARNELL
Tel (0532) 636311
Telex 55147




HAWNT
Tel 021 784 2485
Telex 338814

LUGTON
Tel 01 348 8247
Telex 25618




RESIN DIPPED TANTALUM ELECTROLYTIC CAPACITORS

SH SERIES

Load life characteristics (at +85% C with W.V. applied)




Temperature characteristics




RESIN DIPPED TANTALUM ELECTROLYTIC CAPACITORS

SH SERIES


Typical curves



Impedance vs Frequency (at +25°C)



Impedance vs Frequency (at -40°C)



Leakage current vs applied d.c. voltage
(after 2 minutes at +25°C)

RADIO RESISTOR
Tel (0462) 57166
Telex 826251

UNITED ELECTRONICS
Tel (0438) 2393
Telex 826080

VSI
Tel (0279) 29666
Telex 81387