

FEATURES

Three 12-bit ADCs
ADC sampling rates up to 170 MHz
12-channel analog input mux
525i/625i component analog input
525p/625p component progressive scan support
720p/1080i/1080p/1250i component HDTV support
Digitizes RGB graphics up to 1600 × 1200 at 60 Hz (UXGA)
VBI data slicer (including teletext)
Simultaneous HDMI and analog video sync processing
Ultralow jitter digital PLL
Quad HDMI Rx
4:1 multiplexed HDMI receiver
HDMI 1.3, DVI 1.0
225 MHz HDMI receiver
Repeater support
High-bandwidth digital content protection (HDCP 1.3)
36-/30-/24-bit deep color support
HDMI 1.3-compatible audio interface (I2S, DSD, DST, Dolby® TrueHD, DTS®-HD master audio, and DTS-HD high resolution audio)
Programmable/adaptive equalizer for cable lengths up to 30 meters
Internal EDID RAM
EDID with HDMI cable power support
CEC support
General
S/PDIF (IEC90658-compatible) digital audio output
Highly flexible output interface
12-bit 4:4:4/8-bit 4:2:2 DDR pixel output interface
Dual STDI function support standard identification
2 any-to-any 3 × 3 color space conversion matrixes
2 programmable interrupt request output pins
Advanced sync processing for robust sync extraction of poor video sources
AV.Link support

APPLICATIONS

Advanced TV
PDP HDTVs
LCD TVs (HDTV ready)
LCD/DLP® rear projection HDTVs
CRT HDTVs

LCoS™ HDTVs
AVR video receivers
LCD/DLP front projectors
HDTV STBs with PVR
CRT HDTVs
DVD recorders with progressive scan input support

GENERAL DESCRIPTION

The ADV7604 is a high quality, single chip, multiformat video decoder, graphics digitizer with an integrated 4:1 multiplexed High-Definition Multimedia Interface (HDMI™) receiver.

The ADV7604 contains one main component processor (CP) that processes YPrPb and RGB component formats, including RGB graphics. The CP also processes the video signals from the HDMI receiver. The ADV7604 can operate in quad HDMI and analog input mode, thus providing simultaneous HDMI and analog video sync processing. This allows for fast switching between HDMI and the ADCs.

The ADV7604 supports the decoding of a component RGB/YPrPb video signal into a digital YCrCb or RGB pixel output stream. The support for component video includes 525i, 625i, 525p, 625p, 720p, 1080i, 1080p, and 1250i standards as well as many other HD and SMPTE standards.

Graphics digitization is also supported by the ADV7604. The ADV7604 is capable of digitizing RGB graphics signals from VGA to UXGA rates and converting them into a digital RGB or YCrCb pixel output stream.

The ADV7604 incorporates a quad input HDMI 1.3-compatible receiver that supports all HDTV formats up to 1080p and display resolutions up to UXGA (1600 × 1200 at 60 Hz). The reception of encrypted video is possible with the inclusion of HDCP. The HDMI receiver also includes programmable/adaptive equalization that ensures robust operation of the interface with cable lengths up to 30 meters. The HDMI receiver has advanced audio functionality, such as a mute controller that prevents audible extraneous noise in the audio output.

Fabricated in an advanced CMOS process, the ADV7604 is provided in a space-saving, 260-ball 15 mm × 15 mm BGA surface-mount, RoHS-compliant package and is specified over the -40°C to +70°C temperature range.

For more information on the ADV7604, contact a local Analog Devices, Inc., sales office or email ATV_VIDEORX_INFO@analog.com.

ADV7604

www.DataSheet4U.com

NOTES