

NTES1N02

Product Preview

Power MOSFET 50 mAmps, 20 Volts N-Channel SC-75

- 2.5 V Gate Drive
- Low Threshold Voltage: $V_{th} = 0.5$ to 1.5 V
- High Speed
- Enhancement Mode
- Small Package

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)


Rating	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	20	Vdc
Gate-to-Source Voltage – Continuous	V_{GSS}	10	Vdc
Drain Current – Continuous @ $T_A = 25^\circ\text{C}$	I_D	50	mA _{dc}
Total Power Dissipation @ $T_A = 25^\circ\text{C}$	P_D	100	mW
Channel Temperature	T_{ch}	150	$^\circ\text{C}$
Operating and Storage Temperature Range	T_{stg}	-55 to 150	$^\circ\text{C}$



ON Semiconductor™

<http://onsemi.com>

50 mAmps
20 VOLTS
 $R_{DS(on)} = 10 \Omega$




MARKING DIAGRAM



N02 = Device Code
D = Date Code

PIN ASSIGNMENT



ORDERING INFORMATION

Device	Package	Shipping
NTES1N02	SC-75	3000 Tape & Reel

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

NTES1N02

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage (V _{GS} = 0 Vdc, I _D = 100 μA)	V _{(BR)DSS}	20	–	–	Vdc
Drain Cut-off Current (V _{DS} = 20 Vdc, V _{GS} = 0 Vdc)	I _{DSS}	–	–	1.0	μAdc
Gate-Body Leakage Current (V _{GS} = 10 Vdc, V _{DS} = 0)	I _{GSS}	–	–	1.0	μAdc

ON CHARACTERISTICS

Gate Threshold Voltage (V _{DS} = 3.0 Vdc, I _D = 0.1 mAdc)	V _{th}	0.5	–	1.5	Vdc
Drain-to-Source On-Resistance (V _{GS} = 2.5 Vdc, I _D = 10 mAdc)	R _{DS(on)}	–	5.0	10	Ω
Forward Transfer Admittance (V _{DS} = 3.0 Vdc, I _D = 10 mAdc)	Y _{FS}	20	–	–	mS

DYNAMIC CHARACTERISTICS

Input Capacitance	(V _{DS} = 3.0 Vdc, V _{GS} = 0 Vdc, f = 1.0 MHz)	C _{iss}	–	5.5	–	pF
Output Capacitance	(V _{DS} = 3.0 Vdc, V _{GS} = 0 Vdc, f = 1.0 MHz)	C _{oss}	–	25	–	
Reverse Transfer Capacitance	(V _{DS} = 3.0 Vdc, V _{GS} = 0 Vdc, f = 1.0 MHz)	C _{rss}	–	1.6	–	


SWITCHING CHARACTERISTICS

Turn-On Delay Time	(V _{DD} = 3.0 Vdc, I _D = 10 mAdc, V _{GS} = 0 to 2.5 Vdc)	t _{on}	–	0.14	–	μs
Turn-Off Delay Time		t _{off}	–	0.14	–	

NTES1N02

PACKAGE DIMENSIONS


SC-75 (SC-90, SOT-416)
CASE 463-01
ISSUE B



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: MILLIMETER.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	0.70	0.80	0.028	0.031
B	1.40	1.80	0.055	0.071
C	0.60	0.90	0.024	0.035
D	0.15	0.30	0.006	0.012
G	1.00 BSC		0.039 BSC	
H	---	0.10	---	0.004
J	0.10	0.25	0.004	0.010
K	1.45	1.75	0.057	0.069
L	0.10	0.20	0.004	0.008
S	0.50 BSC		0.020 BSC	

- STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)
Email: ONlit@hibbertco.com

EUROPEAN TOLL-FREE ACCESS*: 00-800-4422-3781

*Available from Germany, France, Italy, UK, Ireland

CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)
Email: ONlit-spanish@hibbertco.com
Toll-Free from Mexico: Dial 01-800-288-2872 for Access –
then Dial 866-297-9322

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001-800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.