

KVR266X72RC25L/1G
1024MB 128M x 72-Bit DDR266
CL2.5 Registered 184-Pin ECC DIMM


DESCRIPTION:

This document describes ValueRAM's 128M x 72-bit (1024MB) CL2.5 SDRAM (Synchronous DRAM) Registered low profile DDR266 ECC memory module. The components on this module include eighteen stacked 128M x 4-bit, 133MHz, 7.5ns, CL2.5 SDRAM and three 16-bit drivers in TSSOP packages. This 184-pin DIMM uses gold contact fingers and requires +2.5V. The electrical and mechanical specifications are as follows:


FEATURES:

✓	Clock Cycle Time (tCK)	7.5ns (min.) / 12ns (max.)
✓	Row Cycle Time (tRC)	65ns (min.)
✓	Refresh Row Cycle Time (tRFC)	75ns (min.)
✓	Row Active Time (tRAS)	45ns (min.) / 120,000ns (max.)
✓	Single Power Supply of	+2.5V (+/- .25V)
✓	Power (IDD0)	8.900 W (operating)
✓	UL Rating	94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here. However, in no configuration will the module height exceed 1.200" (30.48mm).



COMP SIDE



SOLDER SIDE— MIRRORED




Figure 1: KVR266X72RC25L/1G 184-Pin DDR SDRAM Module