

## Silicon NPN Power Transistors

## BUS14A

## DESCRIPTION


- With TO-3 package
- High voltage ,high speed

## APPLICATIONS

- Converters
- Inverters
- Switching regulators
- Motor controls

## PINNING (See Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector

Absolute maximum ratings( $T_a=25^{\circ}\text{C}$ )

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
$V_{CBO}$	Collector-base voltage	Open emitter	1000	V
$V_{CEO}$	Collector-emitter voltage	Open base	450	V
$V_{EBO}$	Emitter-base voltage	Open collector	9	V
$I_C$	Collector current		30	A
$I_{CM}$	Collector current-Peak		50	A
$I_B$	Base current		6	A
$I_{BM}$	Base current-Peak		10	A
$P_T$	Total power dissipation	$T_{mb}=25^{\circ}\text{C}$	250	W
$T_j$	Junction temperature		200	$^{\circ}\text{C}$
$T_{stg}$	Storage temperature		-65~200	$^{\circ}\text{C}$

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
$R_{th\ j-mb}$	Thermal resistance from junction to mounting base	0.7	$^{\circ}\text{C}/\text{W}$

## Silicon NPN Power Transistors

## BUS14A

## CHARACTERISTICS

T<sub>j</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>CEO(SUS)</sub>	Collector-emitter sustaining voltage	I <sub>C</sub> =0.1A ; I <sub>B</sub> =0; L=25mH	450			V
V <sub>CE(sat)</sub>	Collector-emitter saturation voltage	I <sub>C</sub> =16A; I <sub>B</sub> =3.2A			1.5	V
V <sub>BE(sat)</sub>	Base-emitter saturation voltage	I <sub>C</sub> =16A; I <sub>B</sub> =3.2A			1.7	V
I <sub>CES</sub>	Collector cut-off current	V <sub>CE</sub> =RatedBV <sub>CEO</sub> ; V <sub>BE</sub> =0 T <sub>C</sub> =125°C			1 5	mA
I <sub>EBO</sub>	Emitter cut-off current	V <sub>EB</sub> =9V; I <sub>C</sub> =0			10	mA
h <sub>FE</sub>	DC current gain	I <sub>C</sub> =2A ; V <sub>CE</sub> =5V	15		50	

## Switching times

t <sub>on</sub>	Turn-on time	I <sub>C</sub> =16A; I <sub>B1</sub> =- I <sub>B2</sub> =3.2A			1.0	μ s
t <sub>s</sub>	Storage time				4.0	μ s
t <sub>f</sub>	Fall time				0.8	μ s

Silicon NPN Power Transistors

BUS14A

PACKAGE OUTLINE




Fig.2 Outline dimensions