



- ▶ Housing designed for Angle PC application
- ▶ Uses a zirconia ferrule having a conical tip optimal for angle PC polishing
- ▶ Angled endface shape for easier polishing
- ▶ Keying width: 2.14 + 0/-0.05 mm (N type); 2.02+0/-0.05 (R type)
- ▶ Complies with Telcordia specification GR-326-CORE (excluding Ø 0.9 mm rubber hood type)
- ▶ Combined with SNA-1/3/4 (Adaptor) provides low insertion loss and ultra high return loss
- ▶ Satisfy Vertical Burning Test for Classifying Materials UL94V-0 (excluding cap)

ORDERING INFORMATION

Model Number	Type Number									
SNP-8	8	7	1	2	5	1	B	3	0	1

Hood Color	
0	Black
8	Green

Hood I.D. (mm)	
1	0.9 mm (flame-resistant rubber)
7	3.0 mm (Plastic)
6	2.0 mm (Plastic)
9	0.9 mm (Plastic)

Ferrule I.D. (µm)	
ø 125, ø 126	

Marking of Hood		
	Applicable Hood(mm)	
0	Without Marking	0.9 mm (flame-resistant rubber)
1	SII Marking	0.9~3.0 mm (Plastic)

Specification	
01	Cutout frame N type
D1	Molded frame N type
J1	Cutout frame R type
K1	Molded frame R type

Package	
1	Individual Package
3	Bulk Package

Cap	
0	No Cap
8	Green PVC
B	Green Ferrule Cap

Plug

SNP-8 Series
Angle PC Application
Easy Assembly
Designed for
ø 0.9 mm Buffer Cable
ø 2.0 mm Cable
ø 3.0 mm Cable
Single Mode

- ▶ Easy installation in equipment panels
- ▶ Precision sleeve (phosphor bronze/zirconia)
- ▶ Excellent detachability

ORDERING INFORMATION

Model Number	Type Number				
SAA-3	1	2	2	0	0

Slit Sleeve	
1	Phosphor Bronze
2	Zirconia

(Required)
0 0

Marking	
1	Without Marking
2	SAA-3 JAPAN SII

Cap	
1	White (plastic)
2	Red (synthetic rubber)



Adaptor

SAA-3 Series
Single Mode