

Power Line Filters Single Stage

62-PPF/PQF/PRF Series



Tested and found to be
IAW VDE 0565 Part 3

Features


- Low-cost plastic case
- Compact design requires minimal real estate space
- Suitable for products that must conform to FCC and FTZ regulations
- Wide variety of circuit and filtering options
- Good filtering characteristics for both normal mode and common mode
- Epoxy molded for reliability
- Operating temperature: -25°C to +85°C (including temperature rise, see graph on page 63)

Applications

- Personal computers and peripherals
- Digital equipment
- Industrial equipment
- Vending machines
- Office equipment



Circuit Diagrams



* Bleeder Resistor is available only for
62-P(Q/R/P)F-XXX-X-12

Specifications

Model	Rated Voltage (@ 50/60Hz)	Rated Current	Leakage Current (Max.)	Capacitance		Inductance (L ₁)	Temperature Rise (Max.)			
				C _Y	C _X					
62-PQF-020-5-11	250VAC	2A	0.50mA	3300pF	0.1uF	15mH	30°C			
62-PQF-020-5-12					.22uF					
62-PPF-020-5-11					0.1uF			8mH		
62-PPF-020-5-12					.22uF					
62-PQF-030-5-11					0.1uF				2.1mH	
62-PQF-030-5-12					.22uF					
62-PPF-030-5-11		0.1uF			486uH					
62-PPF-030-5-12		.22uF								
62-PQF-060-5-11		0.1uF				181uH				
62-PQF-060-5-12		.22uF								
62-PPF-060-5-11		0.1uF						97uH		
62-PPF-060-5-12		.22uF								
62-PRF-010-5-11		1A			3A				0.1uF	.22uF
62-PRF-010-5-12		2A								
62-PRF-020-5-11		2A			3A	0.1uF			.22uF	
62-PRF-020-5-12		3A								
62-PRF-030-5-11		3A								
62-PRF-030-5-12										

Note: All types are designed to meet the requirement of UL 1283, CSA 22.2, VDE 0565-3

Test voltage: 1500VAC one minute, line to ground

Insulation resistance: 300 Mohm min. at 500VDC

Voltage drop: 1V max. (except 62-PRF-010-5-11) at rated current

62-PRF-010-5-11: 1.5V max. at rated current



Weight: 62-PPF & PQF Series: 2.11 ounces (60 grams)

62-PRF Series: 1.76 ounces (50 grams)


Power Line Filters Single Stage

62-PPF/PQF/PRF Series


Temperature Characteristics




Normal Mode




62-PQF Series




62-PPF Series



Common Mode



62-P(Q/R)F Series



62-PRF Series

