


CGL


90° Plug, Class PG




CGL08PG-B

with bayonet coupling

CGL08PG-B designates a 90° plug for the use of heat shrink boots or PG terminations. It mates with receptacle CGL02A-B.




Best-Nr.	A	L	W
Socket insert	max.	max.	PG Thread
CGL08PG18-11S-C1L-B	36,5 (1.437)	77 (3.031)	PG16
CGL08PG18-11S-E1-B	36,5 (1.437)	77 (3.031)	PG16
CGL08PG20-3S-B1-B	39,9 (1.571)	77 (3.031)	PG16
CGL08PG20-17S-C1-B	39,9 (1.571)	82 (3.228)	PG21
CGL08PG22-22S-D1L-B	43,1 (1.697)	82 (3.228)	PG21



CGL08PG

with threaded coupling

CGL08PG designates a 90° plug for the use of heat shrink boots or PG terminations. It mates with receptacle CGL02A.



Part No.	A	E	L	W
Socket insert	max.	Thread	max.	PG Thread
CGL08PG10SL-3S-C1L-*	22,8 (.898)	5/8-24NEF-2B	65 (2.559)	PG9
CGL08PG18-10S-D1L-*	36,5 (1.437)	1-1/8-18NEF-2B	77 (3.031)	PG16
CGL08PG18-11S-C1L-*	36,5 (1.437)	1-1/8-18NEF-2B	77 (3.031)	PG16
CGL08PG18-11S-E1-*	36,5 (1.437)	1-1/8-18NEF-2B	77 (3.031)	PG16
CGL08PG20-3S-B1-*	39,9 (1.571)	1-1/4-18NEF-2B	77 (3.031)	PG21
CGL08PG20-15S-E1-*	39,9 (1.571)	1-1/4-18NEF-2B	77 (3.031)	PG21
CGL08PG20-17S-C1-*	39,9 (1.571)	1-1/4-18NEF-2B	77 (3.031)	PG21
CGL08PG22-16S-D1-*	43,1 (1.697)	1-3/8-18NEF-2B	82 (3.228)	PG21
CGL08PG22-22S-D1L-*	43,1 (1.697)	1-3/8-18NEF-2B	82 (3.228)	PG21
CGL08PG22-23S-F1L-*	43,1 (1.697)	1-3/8-18NEF-2B	82 (3.228)	PG21