



CAN-Bus Common Mode Chokes

These current compensating surface mount common mode chokes can be used in controller area networks (CAN-Bus) in automotive, industrial and medical applications.

Features:

- Accurate current matching capability over a broad range of inductance values
- Sector wound coils at 25 & 51 μH to filter differential mode noise from the data signal.
- Low distortion
- Custom designs possible
- Open bottom case construction
- Small (1812) size parts are also available.
- Surface Mount

Applications:

- Automotive controller area network systems
- Industrial controls controller area network systems
- Medical monitoring systems
- Filtering common mode EMI on high speed differential lines such as network and telecom applications

PART NUMBER SYSTEM EXAMPLE


CC	1812	C	513	R	-10
Product Series Code	Part Size Code	Rated Current Code	Impedance Value Code	Packaging Code	Additional Description

Operating Temperature Range: -40°C to +125°C (0°C to 125°C for $L_p \geq 1000 \mu\text{H}$)


PART NUMBER	Lp Inductance (μH)				Peak Impedance (Z)	L leakage (μH)	Hi-Pot (VAC) 0.5 mA 2 sec.	DCR Typical (Ω)	Idc (mA)
	Test Conditions	MIN	NOM	MAX					
CC1812C513R-10*	100 KHz / 50 mV	35.7	51.0	66.3	3500 Ω @40 MHz	2.60	250	0.50	200
CC2824J502R-10	100 KHz / 50 mV	3.5	5.0	6.5	400 Ω @500 MHz	0.05	250	0.10	1200
CC2824E113R-10	100 KHz / 50 mV	7.7	11.0	14.3	800 Ω @200 MHz	0.05	250	0.12	800
CC2824E253R-10	100 KHz / 50 mV	17.5	25.0	32.5	2000 Ω @100 MHz	1.50	250	0.13	800
CC2824E513R-10*	100 KHz / 50 mV	35.0	51.0	66.3	3800 Ω @50 MHz	2.00	250	0.16	800
CC2824E474R-10	100 KHz / 50 mV	329.0	470.0	611.0	8600 Ω @5 MHz	0.20	750	0.20	700
CC2824E105R-10	100 KHz / 50 mV	700.0	1000.0	1500.0	4250 Ω @7 MHz	0.20	750	0.20	700
CC2824D225R-10	10 KHz / 50 mV	1540.0	2200.0	3300.0	5300 Ω @5 MHz	0.25	750	0.40	500
CC2824B475R-10	10 KHz / 50 mV	3290.0	4700.0	7050.0	12300 Ω @2 MHz	0.30	750	0.55	400

* Sector Wound

PART NUMBER	A mm (inches)	B mm (inches)	C mm (inches)
CC2824	7.50 MAX (0.295 MAX)	5.50 MAX (0.217 MAX)	3.80 MAX (0.150 MAX)
CC1812	5.00 MAX (0.197 MAX)	3.50 MAX (0.138 MAX)	5.55 MAX (0.140 MAX)



CC2824
Surface Mount



CC1812
Surface Mount

Refer to part print for specific dimensions

Typical Insertion Loss @ 50 Ω

