

Cordsets and Patchcords

AC Micro (Dual Keyway) Style Quick-Disconnect Cordset



Specifications

Coupling Nut	Nickel-plated brass
Connector	Molded oil-resistant PVC
Contacts	Gold-plated palladium/nickel
Cable	Yellow oil-resistant PVC jacket, 22AWG conductors, 300V, UL recognized and CSA certified
Cable O.D.	7.4mm (0.29in)
Enclosure Rating	IP 67, NEMA 6P
Temperature	-20°C to +105°C (-4°F to +221°F)


Features

- UL recognized and CSA certified
- Highly visible yellow PVC jacket offers good oil and chemical resistance

Product Selection

Female Connector (Sensor End)		Cable			Catalogue Number
Face View of Female	Connector Style	Wire Colour	Wire Rating	Length—m (ft)	
	Straight	1 Red/White Tr.	22AWG 300V 3A	2 (6.5)	889R-F6ACA-2
		2 Red		5 (16.4)	889R-F6ACA-5
		3 Green		10 (32.8)	889R-F6ACA-10
		4 Red/Yellow Tr.			
		5 Red/Black Tr.			
		6 Red/Blue Tr.			

Approximately Dimensions—mm (inches)



Straight Female

Dimensions are approximate. Illustrations are not drawn to scale.