


Rectifier Diode SXXHN/HR26





Symbol	Characteristics	Conditions	$T_J(^{\circ}\text{C})$	Value	Unit
BLOCKING PARAMETERS					
V_{RRM}	Repetitive peak reverse voltage		180	200-1500	V
I_{RRM}	Repetitive peak reverse current	$V = V_{RRM}$	180	4	mA
CONDUCTING PARAMETERS					
$I_{F(AV)}$	Average on-state current	180 sine, 50Hz, $T_C = 130^{\circ}\text{C}$		25	A
I_{RMS}	RMS on-state current			40	A
I_{FSM}	Non repetitive peak surge on-state current	Sine wave, 10mS without reverse voltage	180	400	A
I^2t	Permissible surge energy			800	A ² S
V_{FM}	Peak on-state voltage drop	On-state current = 78A	180	1.25	V
V_0	Typical forward conduction Threshold voltage		180	0.80	V
r_0	Typical forward slope resistance		180	4.25	m Ω
THERMAL & MECHANICAL PARAMETERS					
$R_{TH(J-C)}$	Thermal impedance, 180 ^o conduction, Sine	Junction to case		1.00	^o C/W
$R_{TH(C-HK)}$	Thermal impedance	Case to heatsink		0.25	^o C/W
T_J	Maximum Permissible junction temperature			180	^o C
T_{STG}	Storage temperature range			-40 – 180	^o C
F	Mounting Torque			3	NM
W	Weight			40	gms




HIND RECTIFIERS LTD

Rectifier Diode SXXHN/HR26




All dimensions in mm


On State Power Loss




Rectifier Diode SXXHN/HR26




Maximum Permissible Case Temp




Max non repetitive Surge Current







Transient Thermal Impedance Junction to Case



On State Characteristics



Rectifier Diode SXXHN/HR26



Ordering Information: -

S	XX	HN / HR	26
Hirect make Rectifier Diode	$V_{RRM} = XX * 100$ e.g. 12 * 100 = 1200V	HN – Normal Polarity HR – Reverse Polarity	$I_{F(AV)} = 26A$

Hind Rectifiers Ltd reserves the right to change the specifications without notice.

This datasheet specifies technical information for semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

Hind Rectifiers Ltd

Lake Road

Bhandup (West)

Mumbai – 400 078

Tel: - +91 22 2596 8027/28/29/31

Fax: - +91 22 2596 4114

E-mail: - marketing@hirect.com

Website: - www.hirect.com

June-2008



HIND RECTIFIERS LTD

5 of 5