



1201-24-9

REVISIONS	
ISSUE	CHANGES
0	ER 36280 KH 05/04/95
1	CN 36939 A KH 04/23/96
C	ER 34758 COL 09/06/11

CUSTOMER
SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS. NO REPRODUCTION OR DISCLOSURE TO ANYONE IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

USED ON

CAGE CODE:918336

JACK, PANEL, N

DRAWN	DATE
KH	04/27/94
DESIGN	DATE
JT	04/28/94
APPR.	DATE

WINCHESTER ELECTRONICS CORPORATION
62 Berris Industrial Road North
Wallingford, CT 06492

1201-24-9

- NOTES:
- FOR USE WITH BOEING BMS13-65 OJ & ADAMS RUSSELL FC38Z CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-546-2.
 - FOR CRIMPING USE DIE KTH-2213.
 - INTERFACE PER MIL-STD-348, FIG. 304-2.
 - FOR USE WITH .22 MAX. PANEL.
 - CENTER CONTACT (1-534-85MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 1201-24-9 XX XX (DATE CODE)
 - MATERIALS:
INSULATOR: TEFLON, ASTM-D-1710
K-GRIP SLEEVE: COM. BRONZE, ASTM-B135
CENTER CONTACT: BER. COP., ASTM-B196
ALL OTHER PARTS: BRASS, ASTM-B16
 - FINISHES:
CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(ROHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(ROHS)
 - ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz
 - WEIGHT: 40.3 GRAMS(0.089 POUNDS)