

Features


- Small Size, Low Profile
- Superior Repeatability (Lot-to-Lot Variation)
- Typical Isolation 25 dB
- Typical Insertion Loss 1.0 dB
- Low Cost
- SOIC-16 Package

Description

M/A-COM's DS56-0006 is an IC-based monolithic power splitter/combiner in a low cost SOIC-16 plastic package. This 6-way power divider is ideally suited for applications where PCB real estate is at a premium and standard packaging for automated assembly and low cost are critical. Typical applications include base stations, portables, and peripheral devices (PCMCIA cards) for wireless standards such as PCS, PCN, DECT, PHS, and DCS-1800. Available in Tape and Reel.

The DS56-0006 is fabricated using passive-integrated circuit process. This process features full-chip passivation for increased performance and reliability.

Functional Block Diagram¹



1. All unused pins must be RF and DC grounded.

Ordering Information

Part Number	Package
DS56-0006	Bulk Packaging
DS56-0006-TR	1000 piece reel

Note: Reference Application Note M513 for reel size information.

Pin Configuration

Pin No.	Function	Pin No.	Function
1	GND	9	GND
2	RF 3 (OUT)	10	GND
3	GND	11	RF 6 (OUT)
4	RF 2 (OUT)	12	GND
5	GND	13	RF 5 (OUT)
6	RF 1 (OUT)	14	GND
7	GND	15	RF 4 (OUT)
8	RF IN	16	GND

Electrical Specifications: $T_A = 25^\circ\text{C}$, $Z_0 = 50\Omega$

Parameter	Units	Min	Typ	Max
Insertion Loss above 7.8 dB 1700 – 2000 MHz 1850 – 1910 MHz	dB	—	1.3	1.8
	dB	—	1.0	1.5
Isolation 1700 – 2000 MHz 1850 – 1910 MHz	dB	18	25	—
	dB	21	26	—
VSWR Input 1700 – 2000 MHz 1850 – 1910 MHz Output 1700 – 2000 MHz 1850 – 1910 MHz	—	—	1.7:1	2.0:1
	—	—	1.3:1	1.7:1
	—	—	1.3:1	1.7:1
	—	—	1.1:1	1.3:1
Amplitude Balance 1700 – 2000 MHz 1850 – 1910 MHz	dB	—	0.8	1.3
	dB	—	1.0	1.3
Phase Balance 1700 – 2000 MHz 1850 – 1910 MHz	Deg.	—	10	20
	Deg.	—	8	16

Absolute Maximum Ratings ^{2,3}

Parameter	Absolute Maximum
Input Power ⁴	1 W CW
Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to +150°C

- Exceeding any one or combination of these limits may cause permanent damage to this device.
- M/A-COM does not recommend sustained operation near these survivability limits.
- With internal load dissipation of 0.125 W maximum.

Handling Procedures


Please observe the following precautions to avoid damage:

Static Sensitivity


GMIC Circuits are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.

Typical Performance Curves


Insertion Loss vs. Frequency




Amplitude Imbalance vs. Frequency




Isolation vs. Frequency




Phase Imbalance vs. Frequency




Input VSWR vs. Frequency



Output VSWR vs. Frequency



SOIC-16[†]



[†] Reference Application Note M538 for lead-free solder reflow recommendations.