

## HEX SCHMITT TRIGGERS

## ■ DESCRIPTION

The **CD40106** is a high speed Si-gate CMOS device which contains six independent Schmitt-trigger inverters and they perform the function  $Y=A$ .


The device have different input threshold levels for positive-going ( $V_{T+}$ ) and negative-going( $V_{T-}$ ) signals because of the Schmitt-trigger action in the input.


## ■ FEATURES


- \* High voltage type (20V rating)
- \* All inputs have Schmitt-trigger action
- \* Hysteresis Voltage(TYP): 0.9V at  $V_{CC}=5V$   
2.3V at  $V_{CC}=10V$   
3.5V at  $V_{CC}=15V$
- \* Wide supply voltage range from 3V to 18V
- \* Inputs are TTL-Voltage compatible
- \* Noise immunity greater than 50%

## ■ ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
CD40106L-S14-R	CD40106G-S14-R	SOP-14	Tape Reel


CD40106G-S14-T 	(1)R: Tape Reel (2)S14: SOP-14 (3)L: Lead Free, G: Halogen Free
---	---



**■ PIN CONFIGURATION****■ FUNCTION TABLE (each gate)**

INPUT	OUTPUT
A	Y
L	H
H	L

Note: H: HIGH voltage level; L: LOW voltage level

**■ LOGIC DIAGRAM (positive logic)**

ABSOLUTE MAXIMUM RATING ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)(Note 1)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V_{CC}$	-0.5 ~ 20	V
Input Voltage	$V_{IN}$	-0.5 ~ $V_{CC} + 0.5$	V
DC Input Current, Any One Input	$I_{IN}$	$\pm 10$	mA
Power Dissipation	$P_D$	500	mW
Storage Temperature	$T_{STG}$	-65 ~ +150	$^\circ\text{C}$

Note 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

### ■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	$V_{CC}$	Operating	3	18	V	
Input Voltage	$V_{IN}$		0	$V_{CC}$	V	
Operating Temperature	$T_{OPR}$		-40	+85	$^\circ\text{C}$	

### ■ STATIC CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Positive-Going Input Threshold Voltage	$V_{T+}$	$V_{CC}=5\text{V}$	2.2	2.9	3.6	V
		$V_{CC}=10\text{V}$	4.6	5.9	7.1	
		$V_{CC}=15\text{V}$	6.6	8.8	10.8	
Negative-Going Input Threshold Voltage	$V_{T-}$	$V_{CC}=5\text{V}$	0.9	1.9	2.8	V
		$V_{CC}=10\text{V}$	2.5	3.9	5.2	
		$V_{CC}=15\text{V}$	4.0	5.8	7.4	
Hysteresis Voltage ( $V_{T+}-V_{T-}$ ) (see figure 3)	$\Delta V_T$	$V_{CC}=5\text{V}$	0.3	0.9	1.6	V
		$V_{CC}=10\text{V}$	1.2	2.3	3.6	
		$V_{CC}=15\text{V}$	1.6	3.5	5.0	
High-Level Output Voltage	$V_{OH}$	$V_{CC}=5\text{V},  I_O  < 1\mu\text{A}$	4.95	5		V
		$V_{CC}=10\text{V},  I_O  < 1\mu\text{A}$	9.95	10		
		$V_{CC}=15\text{V},  I_O  < 1\mu\text{A}$	15.95	15		
Low-Level Output Voltage	$V_{OL}$	$V_{CC}=5\text{V},  I_O  < 1\mu\text{A}$		0	0.05	V
		$V_{CC}=10\text{V},  I_O  < 1\mu\text{A}$		0	0.05	
		$V_{CC}=15\text{V},  I_O  < 1\mu\text{A}$		0	0.05	
High-level Output Current	$I_{OH}$	$V_{CC}=5\text{V}, V_O=4.6\text{V}$	-0.51	-1		mA
		$V_{CC}=5\text{V}, V_O=2.5\text{V}$	-1.6	-3.2		
		$V_{CC}=10\text{V}, V_O=9.5\text{V}$	-1.3	-2.6		
		$V_{CC}=15\text{V}, V_O=13.5\text{V}$	-3.4	-6.8		
Low-level Output Current	$I_{OL}$	$V_{CC}=5\text{V}, V_O=0.4\text{V}$	0.51	1.0		mA
		$V_{CC}=10\text{V}, V_O=0.5\text{V}$	1.3	2.6		
		$V_{CC}=15\text{V}, V_O=1.5\text{V}$	3.4	6.8		
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=18\text{V}, V_{IN}=V_{CC}$ or GND		$\pm 0.01$	$\pm 100$	nA
Quiescent Supply Current	$I_{DD}$	$V_{CC}=5\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$	0.02	1		uA
		$V_{CC}=10\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$	0.02	2		
		$V_{CC}=15\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$	0.02	4		
		$V_{CC}=20\text{V}, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$	0.04	20		

■ DYNAMIC CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified; Input:  $t_R, t_F=20\text{ns}$ )


See Fig. 1 and Fig. 2 for test circuit and waveforms.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from input (A) to output(Y)	$t_{PLH}/t_{PHL}$	$V_{CC}=5\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		140	280	ns
		$V_{CC}=10\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		70	140	
		$V_{CC}=15\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		60	120	
Output Transition Time	$t_{TLH}/t_{THL}$	$V_{CC}=5\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		100	200	ns
		$V_{CC}=10\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		50	100	
		$V_{CC}=15\text{V}, C_L=50\text{pF}, R_L=200\text{k}\Omega$		40	80	

■ OPERATING CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Average Input Capacitance	$C_{IN}$	Any Input		5	7.5	pF
Power Dissipation Capacitance	$C_{PD}$	Any Gate		14		pF


■ TEST CIRCUIT AND WAVEFORMS




TEST CIRCUIT

Note:  $C_L$  includes probe and jig capacitance.

Fig. 1 Load circuitry for switching times.



PROPAGATION DELAY TIMES



Output Transition Time

Fig. 2 Propagation delay from input(A) to output(Y) and Output transition time.

## ■ TEST CIRCUIT AND WAVEFORMS(Cont.)




Fig. 3 Hysteresis definition, characteristics, and test setup

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.