

Part Number: C1706

Revision Level: 11/19/2012

**2C 18AWG 16/30BC PP, PVC**
**COMMAND® SERIES**
**A. CONSTRUCTION**

Conductor:	18 AWG 16/30 BC	<b><u>DIAMETERS</u></b>
Insulation:	.009" Wall, Polypropylene (PP)	.047" nom
Cable Core:	2C @ 4.00" LHL	.066" nom
Jacket:	.030" Polyvinyl Chloride (PVC)	.132" nom
Print Legend:	<b>CAROL® -- C1706 -- 2C 18AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8                  CL3 60C -- CSA C/US CMG 80C OR CSA AWM I/II A/B 80C 600V                  FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)</b>	

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

**C. ELECTRICAL PROPERTIES**

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	6.55 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	18.8 pF/ft @ 1kHz (nom)

**D. COLOR CODE**

Item	COLOR
1	BLACK
2	RED

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_