

#### General ordering data

Order No.	0225560000
Part designation	ASK 1/EN LD 1D 115VAC
Version	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
EAN	4008190163419
Qty.	25 pc(s).

#### Product notes

Note, technical data	Note: max. conductor size = 2.5 mm <sup>2</sup> when using the cross-connection. Twin wire-end ferrules ZH 0.5 - ZH 2.5 can be used.
----------------------	--------------------------------------------------------------------------------------------------------------------------------------

#### Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	Yes
Installation advice	TS 35 + TS 32
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Fuse terminal

#### CSA rating data

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

#### Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	9 mm
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Tightening torque range	0.6...0.8 Nm
Torque level with DMS electric screwdriver	2
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	4 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.13 mm <sup>2</sup>
AWG conductor size, max.	3.31 mm <sup>2</sup>

#### Dimensions

Width	8.1 mm
Height of lowest version	43 mm
Length	58 mm
TS 32 offset	10.5 mm
TS 35 offset	8.5 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	2
--------------------------------------------	---

#### Display element

Operating voltage for display, max.	115 V
Type of voltage for indicator	AC

#### Fuse terminals

Cartridge fuse	G-Si. 5 x 20
Display	LED
Fuse holder (cartridge holder)	Pivoting
Operating voltage, max.	115 V
Type of voltage for indicator	AC

#### Rating data

Rated cross-section	4 mm <sup>2</sup>
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	6.3 A
Current with max. conductor	6.3 A
Pollution severity	3

#### UL rating data

Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

## Approvals

Approvals institutes



## Classifications

ETIM 2.0	EC000899
ETIM 3.0	EC000899
eClass 4.1	27-14-11-16
eClass 5.0	27-14-11-16
eClass 5.1	27-14-11-16

## Similar products

Order No.	Part designation	Version
0474560000	ASK 1/EN	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
8148930000	KDKS1/EN LD 24 VAC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0222860000	ASK 1/EN LD 1D 24VAC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0222760000	ASK 1/EN LD 15K 24VDC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0225360000	ASK1LD-48A	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0225260000	ASK 1/EN LD 27K 48VDC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0226460000	ASK1LD-60D	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0225460000	ASK 1/EN LD 56K 115VDC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
0225660000	ASK 1/EN LD 120K 230VDC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
8146450000	KDKS1/EN LD 24VDC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32
8148910000	KDKS1/EN LD 230VAC	Fuse terminal, 4 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35 + TS 32