

## Input/Output Full-Swing High Output Current Quad C-MOS Operational Amplifier

### ■ GENERAL DESCRIPTION

The NJU7044 is a quad C-MOS operational amplifier permitting a full-swing input and output in full-swing under high load.


Based on C-MOS technology, there are excellent features such as high output current, low current consumption, low operating voltage, and very high input impedance.

### ■ FEATURES


- Operating Voltage: 2.2V to 5.5V
- Input/Output Full-Swing
- High Output Current: 40mA at  $V_O=0V$
- Input Offset Voltage:  $V_{IO}=10mV$  max.
- Wide Input Common Mode Voltage Range:  $V_{SS}$  to  $V_{DD}$
- Operating Current:  $I_{DD}=1.4mA$  typ. (at  $V_{DD}=3V$ )
- High Input Impedance:  $1T\Omega$  Typ.
- Low Input Bias Current:  $I_{IB}=1pA$  typ.
- Ground Sensing
- Tiny Package:

NJM7044D : DIP14, NJM7044M : DMP14  
 NJM7044E : EMP14, NJM7044V : SSOP14


### ■ PACKAGE OUTLINE



NJU7044D



NJU7044M




NJU7044E



NJU7044V

### ■ PIN CONFIGURATION



#### Pin Function

- |             |              |
|-------------|--------------|
| 1. OUTPUT 1 | 8. OUTPUT 3  |
| 2. -INPUT 1 | 9. -INPUT 3  |
| 3. +INPUT 1 | 10. +INPUT 3 |
| 4. $V_{DD}$ | 11. $V_{SS}$ |
| 5. +INPUT 2 | 12. +INPUT 4 |
| 6. -INPUT 2 | 13. -INPUT 4 |
| 7. OUTPUT 2 | 14. OUTPUT 4 |

NJU7044D  
 NJU7044M  
 NJM7044E  
 NJU7044V

## ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V_{DD}$	7	V
Common Mode Input Voltage Range	$V_{ICM}$	0 to 7 (Note 1)	V
Differential Input Voltage Range	$V_{ID}$	$\pm 7$	V
Power Dissipation	$P_D$	DIP14 700 DMP14 300, 500(Note 2), 660(Note 3) EMP14 300, 720(Note 2), 1100(Note 3) SSOP14 300, 450(Note 2), 570(Note 3)	mW
Output Sink/Source Current for each one output terminal	$I_{oport}$	$\pm 75$ [ DIP14, DMP14, SSOP14 ]	mA
Sum total of Output Sink/Source Current of all output terminal	$I_{ototal}$	180 [ DIP14, DMP14, SSOP14 ] (Note 4)	mA
Operating Temperature Range	$T_{opr}$	-40 to +85	$^{\circ}C$
Storage Temperature Range	$T_{stg}$	-55 to +125	$^{\circ}C$

(Note 1) For supply voltage less than 7V, the absolute maximum input voltage is equal to the supply voltage.

(Note 2) On the PCB " EIA/JEDEC (76.2x11.43x1.6mm, two layers, FR-4) "

(Note 3) On the PCB " EIA/JEDEC (76.2x11.43x1.6mm, four layers, FR-4) "

(Note 4) It individually takes the absolute value of the sink current and the source current of each output terminal, and it is assumed the sum total.

Calculation type:  $I_{ototal} = |I_{oport1}| + |I_{oport2}| + |I_{oport3}| + |I_{oport4}|$

(Note 5) Do not exceed "Power dissipation:  $P_D$ " in which power dissipation in IC is shown by the absolute maximum rating.

Refer to following Figure 1 and Figure 2 for a permissible loss when ambient temperature ( $T_a$ ) is  $T_a \geq 25^{\circ}C$ .

Figure 1 : Power Dissipation - Ambient Temperature





Figure 2 : Power Dissipation - Ambient Temperature



## ■ OPERATING VOLTAGE ( $T_a = 25^{\circ}C$ )

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V_{DD}$	2.2 to 5.5	V

## ■ ELECTRICAL CHARACTERISTICS

### ●DC CHARACTERISTICS

( $V_{DD}=5V, T_a=25^\circ C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Operating Current	$I_{DD}$	No Signal Apply	-	1.8	2.8	mA
Input Offset Voltage	$V_{IO}$		-	-	10	mV
Input Bias Current	$I_B$		-	1	-	pA
Input Offset Current	$I_{IO}$		-	1	-	pA
Large Signal Voltage Gain	$A_V$	$R_L=10k\Omega$ to 2.5V, $V_O=2.5V\pm 2.4V$	70	90	-	dB
Common Mode Rejection Ratio	CMR	CMR+: $2.5V \leq V_{CM} \leq 5V$ CMR-: $0V \leq V_{CM} \leq 2.5V$ (Note 6)	44	60	-	dB
Supply Voltage Rejection Ratio	SVR	$4.0V \leq V_{DD} \leq 5.5V,$ $V_{CM}=V_{DD}/2$	55	85	-	dB
Output Voltage1	$V_{OH1}$	$R_L=10k\Omega$ to 2.5V	4.95	-	-	V
	$V_{OL1}$	$R_L=10k\Omega$ to 2.5V	-	-	0.05	V
Output Voltage2	$V_{OH2}$	$R_L=600\Omega$ to 2.5V	4.88	-	-	V
	$V_{OL2}$	$R_L=600\Omega$ to 2.5V	-	-	0.12	V
Output Source Current	$I_{SOURCE}$	$V_O=3.5V$ (Note 7)	50	-	-	mA
Output Sink Current	$I_{SINK}$	$V_O=1.5V$ (Note 7)	50	-	-	mA
Input Common Mode Voltage Range	$V_{ICM}$	CMR $\geq 44dB$	0	-	5	V

(Note 6) CMR is represented by either CMR+ or CMR- has lower value.

(Note 7) Please note the output current value to exceed neither  $I_{oport}$  nor  $I_{ototal}$  the absolute maximum rating.

### ●AC CHARACTERISTICS

( $V_{DD}=5V, T_a=25^\circ C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Unity Gain Bandwidth	GB	$R_L=10k\Omega$ to 2.5V	-	0.8	-	MHz
Total Harmonic Distortion	THD	$f=1kHz, V_O=0.7V_{rms}, A_V=+1,$ $R_L=10k\Omega$ to 2.5V	-	0.001	-	%
Equivalent Input Noise Voltage	$V_{NI}$	$f=1kHz$	-	40	-	nV/ $\sqrt{Hz}$
Amp to Amp Separation	CS	$f=1kHz, V_O=3V_{pp}$ $R_L=10k\Omega$ to 2.5V	-	120	-	dB

### ●TRANSIENT CHARACTERISTICS

( $V_{DD}=5V, T_a=25^\circ C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Slew Rate	SR	$R_L=10k\Omega$ to 2.5V	-	0.8	-	V/ $\mu s$

# NJU7044

www.DataSheet4U.com

## ■ ELECTRICAL CHARACTERISTICS

### ●DC CHARACTERISTICS

( $V_{DD}=3V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Operating Current	$I_{DD}$	No Signal Apply	-	1.4	2.4	mA
Input Offset Voltage	$V_{IO}$		-	-	10	mV
Input Bias Current	$I_B$		-	1	-	pA
Input Offset Current	$I_{IO}$		-	1	-	pA
Large Signal Voltage Gain	$A_V$	$R_L=10k\Omega$ to 1.5V, $V_O=1.5V\pm 1.4V$	70	90	-	dB
Common Mode Rejection Ratio	CMR	CMR+: $1.5V \leq V_{CM} \leq 3V$ CMR-: $0V \leq V_{CM} \leq 1.5V$ (Note 8)	42	60	-	dB
Supply Voltage Rejection Ratio	SVR	$2.7V \leq V_{DD} \leq 4.0V,$ $V_{CM}=V_{DD}/2$	50	80	-	dB
Output Voltage1	$V_{OH1}$	$R_L=10k\Omega$ to 1.5V	2.95	-	-	V
	$V_{OL1}$	$R_L=10k\Omega$ to 1.5V	-	-	0.05	V
Output Voltage2	$V_{OH2}$	$R_L=600\Omega$ to 1.5V	2.9	-	-	V
	$V_{OL2}$	$R_L=600\Omega$ to 1.5V	-	-	0.1	V
Output Source Current	$I_{SOURCE}$	$V_O=1.5V$	30	40	-	mA
Output Sink Current	$I_{SINK}$	$V_O=1.5V$	30	40	-	mA
Input Common Mode Voltage Range	$V_{ICM}$	CMR $\geq 42dB$	0	-	3	V

(Note 8) CMR is represented by either CMR+ or CMR- has lower value.

### ●AC CHARACTERISTICS

( $V_{DD}=3V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Unity Gain Bandwidth	GB	$R_L=10k\Omega$ to 1.5V	-	0.8	-	MHz
Total Harmonic Distortion	THD	$f=1kHz, V_O=0.35V_{rms}, A_V=+1,$ $R_L=10k\Omega$ to 1.5V	-	0.002	-	%
Equivalent Input Noise Voltage	$V_{NI}$	$f=1kHz$	-	40	-	nV/ $\sqrt{Hz}$
Amp to Amp Separation	CS	$f=1kHz, V_O=1.8V_{pp}$ $R_L=10k\Omega$ to 1.5V	-	115	-	dB

### ●TRANSIENT CHARACTERISTICS

( $V_{DD}=3V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Slew Rate	SR	$R_L=10k\Omega$ to 1.5V	-	0.7	-	V/ $\mu s$

●DC CHARACTERISTICS

(V<sub>DD</sub>=2.2V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Operating Current	I <sub>DD</sub>	No Signal Apply	-	1.2	2	mA
Input Offset Voltage	V <sub>IO</sub>		-	-	10	mV
Input Bias Current	I <sub>B</sub>		-	1	-	pA
Input Offset Current	I <sub>IO</sub>		-	1	-	pA
Large Signal Voltage Gain	A <sub>V</sub>	R <sub>L</sub> =10kΩ to 1.1V, V <sub>O</sub> =1.1V±1.0V	70	90	-	dB
Common Mode Rejection Ratio	CMR	CMR+: 1.1V ≤ V <sub>CM</sub> ≤ 2.2V CMR-: 0V ≤ V <sub>CM</sub> ≤ 1.1V (Note 9)	30	60	-	dB
Supply Voltage Rejection Ratio	SVR	2.2V ≤ V <sub>DD</sub> ≤ 2.7V, V <sub>CM</sub> =V <sub>DD</sub> /2	45	70	-	dB
Output Voltage1	V <sub>OH1</sub>	R <sub>L</sub> =10kΩ to 1.1V	2.15	-	-	V
	V <sub>OL1</sub>	R <sub>L</sub> =10kΩ to 1.1V	-	-	0.05	V
Output Voltage2	V <sub>OH2</sub>	R <sub>L</sub> =600Ω to 1.1V	2.1	-	-	V
	V <sub>OL2</sub>	R <sub>L</sub> =600Ω to 1.1V	-	-	0.1	V
Output Source Current	I <sub>SOURCE</sub>	V <sub>O</sub> =1.1V	10	15	-	mA
Output Sink Current	I <sub>SINK</sub>	V <sub>O</sub> =1.1V	10	15	-	mA
Input Common Mode Voltage Range	V <sub>ICM</sub>	CMR ≥ 30dB	0	-	2.2	V

(Note 9) CMR is represented by either CMR+ or CMR- has lower value.

●AC CHARACTERISTICS

(V<sub>DD</sub>=2.2V, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Unity Gain Bandwidth	GB	R <sub>L</sub> =10kΩ to 1.1V	-	0.8	-	MHz
Total Harmonic Distortion	THD	f=1kHz, V <sub>O</sub> =0.18Vrms, A <sub>V</sub> =+1, R <sub>L</sub> =10kΩ to 1.1V	-	0.004	-	%
Equivalent Input Noise Voltage	V <sub>NI</sub>	f=1kHz	-	40	-	nV/√Hz
Amp to Amp Separation	CS	f=1kHz, V <sub>O</sub> =1.2Vpp R <sub>L</sub> =2kΩ to 1.1V	-	110	-	dB


●TRANSIENT CHARACTERISTICS

(V<sub>DD</sub>=2.2V, Ta=25°C)


PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Slew Rate	SR	R <sub>L</sub> =10kΩ to 1.1V	-	0.6	-	V/μs

•Typical Characteristics


**Supply Current vs. Supply Voltage**  
(Ambient Temperature)




**Supply Current vs. Ambient Temperature**




**Input Offset Voltage vs. Supply Voltage**  
(Ambient Temperature)




**Input Offset Voltage vs. Ambient Temperature**



**Input Offset Voltage vs. Input Common Mode Voltage**




**Maximum Output Voltage vs. Ambient Temperature**




• Typical Characteristics


**Maximum Output Voltage vs. Output Current**  
(Ambient Temperature)  
 $V_{DD}/V_{SS}=\pm 1.5V$ ,  $G_V=OPEN$




**Maximum Output Voltage vs. Capacitive Load**  
(Ambient Temperature)  
 $V_{DD}/V_{SS}=\pm 1.5V$ ,  $G_V=OPEN$



**Maximum Output Voltage vs. Output Current**  
 $G_V=OPEN$ ,  $T_a=+25^\circ C$




**Maximum Output Voltage vs. Capacitive Load**  
(Supply Voltage)  
 $G_V=OPEN$ ,  $T_a=+25^\circ C$




**Common Mode Rejection Ratio vs. Ambient Temperature**

CMR - :  $GND \leq V_{CM} \leq V_{DD}/2$








**Supply Voltage Rejection Ratio vs. Ambient Temperature**

No Signal,  $A_v=0dB$









•Typical Characteristics









•Typical Characteristics



•Typical Characteristics



[CAUTION]  
 The specifications on this data book are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this data book are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.