



MHV Male Connector Crimp/Solder Attachment For RG59, RG62

TECHNICAL DATA SHEET

PE4075

MHV Male Connector Crimp/Solder Attachment For RG59, RG62

Configuration

Connector	MHV Male
Connector Specification	MIL-STD-348A
Connector Interface Type	RG59, RG62
Cable Attachment Method (Shield/Contact)	Crimp/Solder
Body Style	Straight

Electrical Specifications

Frequency Range, MHz	DC to 300
Impedance, Ohms	50
Maximum VSWR	1.3:1
Maximum Operating Voltage, Volts	500
Dielectric Withstanding Voltage, Vrms	1,500

Mechanical Specifications

Temperature

Operating Range, deg C	-65 to +165
------------------------	-------------

Size

Length, in [mm]	1.51 [38.35]
Width/Dia., in [mm]	0.57 [14]
Weight, lbs [g]	0.027 [12.25]

Connector

Type	MHV Male
Contact Material and Plating	Brass, Gold
Contact Plating Specification	30µ in. minimum
Body Material and Plating	Brass, Nickel
Body Plating Specification	100µ in. minimum
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MHV Male Connector Crimp/Solder Attachment For RG59, RG62 PE4075](#)

PE4075 CAD Drawing

MHV Male Connector Crimp/Solder Attachment For RG59, RG62

