

Part Number: C3115

Revision: 1/29/2013

2C 22 AWG (7/32) TC PVC, UNSH, PVC
COMMUNICATION AND CONTROL CABLE
A. CONSTRUCTION

Conductor: #22 AWG (7/32) Tinned Copper
 Insulation: .008" Wall, Plenum PVC
 Cable Core: 2C @ 6.00" LHL
 Jacket: .015" Wall, Plenum PVC
 - Ripcord under jacket

DIAMETERS

.029" Nom
 .045" Nom
 .090" Nom
 .120" Nom

Print Legend: **CAROL (R) 22 AWG -- C3115 -- 75C E60233-8 (UL) CL3P -- C(UL) CMP -- ROHS --
 MADE IN USA (date code) (sequential footage)**

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3P
National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

Temperature:	0° to +75°C
Suggested Working Voltage:	300V Max
Conductor DCR:	17.5 Ohms/M' @ 20°C (Max)
Mutual Capacitance:	27.4 pF/ft. @ 1 kHz (Nom)
Impedance:	71.1 Ohms @ 1MHz (Nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	WHITE

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____