


1.0 AMP. Schottky Barrier Rectifier

FEATURES

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability

MECHANICAL DATA

- **Case:**DO-41 Molded plastic
- **Epoxy:**UL94V-0 rate flame retardant
- **Lead:**Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- **Polarity:**Color band denotes cathode end
- **High temperature soldering guaranteed:** 250 °C/10 seconds/0.375", (9.5mm) lead lengths at 5 lbs., (2.3Kg) tension
- **Weight:**0.33grams



ORDERING INFORMATION

Device	Operating Temperature	Package
1N581xCE	-20 °C TO +85 °C	DO-41

Note: x is the index if Voltage Range

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (TA = 25 °C)

Parameter	Symbol	1N5817	1N5818	1N5819	Units
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	20	30	40	V
Working Peak reverse Voltage	V _{RWM}	20	30	40	V
DC Blocking Voltage	V _{DC}	20	30	40	V
RMS Reverse Voltage	V _{r(rms)}	14	21	28	V
Maximum Average Forward Rectified Current (Ta=55 °C)	I _{fav}	1.0	1.0	1.0	A
Non Repetitive Peak Surge Current (1/2 Wave. 60Hz. T _L =70 °C)	I _{fsm}	25	25	25	A
Maximum Instantaneous Reverse Current (T _L =25 °C)	I _r	1.0	1.0	1.0	mA
Maximum Instantaneous Reverse Current (T _L =100 °C)	I _r	10.0	10.0	10.0	mA
Operating & Storage Temperature Range	T _j , T _{strg}	-65 to 125 °C			°C
Forward Voltage (I _f =1.0A)	V _f	0.450	0.550	0.600	V
Typical Junction Capacitance (note 2)	C _j	110	70	70	pF


Notes: 1.Pulse Test-Pulse width=300 μ S, Duty Cycle 2%.

2.Measured at 1MHz and applied Voltage of 4.0 Volts.

3.Thermal Resistance Junction to Lead Vertical PCB Mounting 0.375"(9.5mm) lead lengths.

1.0 AMP. Schottky Barrier Rectifier

DO-41 Unit: mm



DO-41 DIMENSION				
DIM	mm		INCHES	
	MIN	MAX	MIN	MAX
A	4.200	5.200	0.165	0.205
B	2.000	2.700	0.079	0.106
C	0.710	0.86	0.028	0.034
D	25.40	-	1.000	-